BF SUBLISTOP

CAD CAM

B-FLEX
HEAT TRANSFER VINYL

PRODUCT DESCRIPTION

BF SUBLISTOP was created to be applied on garments printed with dye sublimation. It comes with a built-in barrier to prevent the migration of pigments, keeping the material's original color unaltered even after multiple wash cycles.

This product is easy to work with; the sticky polyester carrier allows for fast weeding and easy repositioning of details that might have accidentally been removed. It is also soft and comfortable to wear, even with bulky designs.

Because of its 120 micron thickness, BF SUBLISTOP is soft on any fabric.

APPLICATION TECHNIQUES

- Knockout
- Layering from other series

APPLICATION STEPS

- Cut - 45° blade
- Weed excess material
- Turn on your heat press - heat to 140°C/285°F
- Place your graphic on the garment
- Press it - 140°C/285°F for 10 seconds
- Remove the liner - hot

SIZES

H 50 cm	L	25 mt / 12,5 mt / 5 mt / 1 mt
H 75 cm	L	25 mt (upon request)
H 100 cm	L	25 mt (upon request)
H 150 cm	L	25 mt (upon request)

Comply with regulation REACH n°1907/2006/EU

TECHNICAL DATA

- Film: PU/polyurethane
- Thickness: 120µ (±5%)
- Liner: adhesive PET
- Finish: matte

PLOTTER SETTING

- Cut settings: mirror
- Blade: 45°
- Minimum cut: 0,5 cm

APPLICATION

- Temperature: 140°C - 285°F
- Time: 10''
- Liner removal: hot
- Pressure: medium - 3,5 bar - 50 PSI
- Textile: synthetic, sublimated fabrics

WASH RESISTANCE

First wash after application	*wait 12 hours*
Max wash temperature	*40°C - 104°F*
Dry clean	✗
Dryer	✗

B·FLEX
HEAT TRANSFER VINYL

BF SUBLISTOP

- Prevents the color's pigments migration from the fabric to the film's surface
- Fully opaque
- Neon colors available

BF 700ASU
WHITE SUBLISTOP

BF 728ASU
LEMON YELLOW SUBLISTOP

BF 720ASU
MEDIUM YELLOW SUBLISTOP

BF 734ASU
ORANGE SUBLISTOP

BF 730ASU
RED SUBLISTOP

BF 792ASU
GOLD SUBLISTOP

BF 796ASU
SILVER SUBLISTOP

BF FLUO20ASU
NEON YELLOW SUBLISTOP

BF FLUO30ASU
NEON ORANGE SUBLISTOP

BF FLUO40ASU
NEON PINK SUBLISTOP

BF FLUO50ASU
NEON GREEN SUBLISTOP