

VISCOM - RI-MARK

Issue date : 05/01/2005  
Date last modification : 17/12/2014**03529 ETCH GLASS PTA/PTAS/PTF SERIES ASP26 PERMANENT WK120****Face Material**

Self-adhesive material for plotter. Polymeric translucent vinyl with metallic flakes.

|                   |                             |            |
|-------------------|-----------------------------|------------|
| Type              | Translucent polymeric vinyl |            |
| Colour and Finish | 3 colours available         |            |
| Weight            | 100 g/m <sup>2</sup> ±10%   | ISO-536    |
| Thickness         | 80 µ ±10%                   | ISO 534-80 |

**Adhesive**

Permanent solvent acrylic featuring high cohesion and good water resistance.

|                  |                            |
|------------------|----------------------------|
| Reference        | ASP26 permanent            |
| Type             | Acrylic permanent          |
| Min. Appl. Temp. | +10°C                      |
| Service Temp.    | -20°C/+130°C               |
| Shear            | High                       |
| Tack             | Medium N/inch <sup>2</sup> |
| Final Adhesion   | High N/inch                |

**Liner**

|                   |  |                  |
|-------------------|--|------------------|
| Type              | One side siliconised clay coated Kraft |                  |
| Colour and Finish | White                                  |                  |
| Weight            | 120 g/m <sup>2</sup> ±10%              | PP-032 - ISO 536 |
| Thickness         | 108 µ ±10%                             | ISO 534          |
| Transparency      | n.a. %                                 | DIN 53 147-64    |

**Applications**

Translucent Etch simulation effect for glass decoration. 5 years outdoor durability. Durability is given in good faith based on simulated weathering tests and real life vertical exposure in non-extreme mid-European conditions.

**Printing Methods**

Not printable.  
Testing for suitability between media, printers and inks is always recommended prior to use.

**Shelf life**

36 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.



Ritrama S.p.A.

Via Senatore Simonetta, 24  
20867 Caponago (MB) ITALY  
e-mail: info@ritrama.com  
www.ritrama.com