



Date of issue : 15/10/2008

Last. mod. date : 10/02/2009

Product code

04584 GEMSTONE 640 SERIES

Description

Self adhesive material for plotter. Cast vinyls with a high concentration of metallic flakes, with 5 years outdoor durability. Excellent dimensional stability. 15 colours available.

Printable in solvent and UV screenprinting.

Permanent solvent acrylic.

It provides dynamic graphic accents and can be used for RV and marine applications, automotive aftermarket graphics and striping, computerized signmaking, tradeshow exhibits and point of purchase displays.

Technical data

FACE MATERIAL

Type	CAST metallic PVC
Colour and Finish	15 colours available
Weight	100g/m ²
Thickness	75μ

ADHESIVE

Reference	US 5
Type	Acrylic Permanent
Min. Appl. Temp.	+10°C
Service Temp.	-10°C/+100°C

RELEASE BACKING

Type	1 side clay-coat
Colour and Finish	White
Weight	135g/m ²
Thickness	150μ

Storage

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of Relative Humidity. Do not expose to direct sun light.

The area must be dry and clean. Please keep the material in the original packaging when not used in order to protect it from dust and contaminations.

All values presented in pdf data sheet are typical. Ritrama's data sheets provide only the general characteristics of the Product. It is the responsibility of the Customer and/or End User to determine that the Product is fit for the purpose for which the Customer and/or End User wish to use it. Ritrama can give no guarantee beyond the information given in the data sheet.