

## PRODUCT DATA SHEET

Product Code: REV4332140050

Issued September 2017



Technical Data Sheet

> Issue date: 05/01/2005 Date last modification: 09/12/2016

**GRAPHICS** - Wide Format Ink Jet Print Media

# 4-GL3C-04060 RI-JET TRANSLUCENT WHITE ASP30 REMOVABLE WK135

### Face Material

Translucent white polymeric vinyl.

Polymeric vinyl Type Colour and Finish Translucent white

ISO-536 Weight 120 g/m<sup>2</sup> ±10% ISO 534-80 **Thickness** 90 µ ±10%

## Adhesive

Solvent based semipermanent adhesive featuring high water resistance. Designed for a wide variety of substrates such as glass, ABS, PS, PVC. Unsuitable for apolar surfaces (like PE and PP).

ASP30 semipermanent Reference Acrylic semipermanent Type

Min. Appl. Temp. +10°C -30°C/+100°C Service Temp. Shear Medium Tack High N/inch<sup>2</sup> Final Adhesion Medium N/inch

Liner

Type One side siliconised clay coated

Kraft

Colour and Finish White

Weight 135 g/m<sup>2</sup> PP-032 - ISO 536 ±10%

145 µ ±10% ISO 534 Thickness DIN 53 147-64 Transparency n.a. %

## **Applications**

Luminous trasmittance in according to DIN EN 166/169/170 is 36,6%.

For advertising and promotional applications (outdoor and indoor posters, billboards and signs) and for vehicle applications (flat sided including buses, trams and taxis). Particularly suitable for illuminated signs and window graphics.

#### **Printing Methods**

The RI-JET series of ink-jet print media gives excellent print results with UV, solvent and eco-solvent ink-jet printing. Testing for suitability between media, printers and inks is always recommended prior to use.

#### Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of  $22^{\circ}C \pm 2^{\circ}C$  and 50  $\pm$ 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.



Ritrama S.p.A. Via Senatore Simonetta, 24 20867 Caponago (MB) ITALY e-mail:info@ritrama.com www.ritrama.com

