



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Beadlock Trim - Ceramic Coating

Version number: GHS 2.0
Replaces version of: 2023-10-27 (GHS 1)

Revision: 2024-04-11

SECTION 1: Identification

1.1 Product identifier

Trade name

Beadlock Trim - Ceramic Coating

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Plastic trim conditioner
Multi-surface protective coating
Professional use
Industrial use

Uses advised against

Do not use for squirting or spraying. Do not use for products which come into direct contact with the skin.

1.3 Details of the supplier of the safety data sheet

Shine Supply
1343 Callens Rd.
Ventura CA 93003

805-535-4332
info@shinesupply.com

1.4 Emergency telephone number

Emergency information service

USA 1.800.535.5053, INTL 1.352.323.3500
24 hour emergency number

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.2	skin corrosion/irritation	1B	Skin Corr. 1B	H314
A.3	serious eye damage/eye irritation	1	Eye Dam. 1	H318
A.4S	skin sensitization	1	Skin Sens. 1	H317
B.6	flammable liquid	2	Flam. Liq. 2	H225

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis. The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Beadlock Trim - Ceramic Coating

Version number: GHS 2.0
Replaces version of: 2023-10-27 (GHS 1)

Revision: 2024-04-11

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS02, GHS05, GHS07



- Hazard statements

H225 Highly flammable liquid and vapor.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.

- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.
P302+P352 If on skin: Wash with plenty of water.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a poison center/doctor.
P321 Specific treatment (see on this label).
P363 Wash contaminated clothing before reuse.
P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling

Cyclosilazanes, di-Me, Me Hydrogen, polymers with di-Me, Me hydrogen silazanes, and 2,4-TDI

2.3 Other hazards

Hazards not otherwise classified

May be harmful in contact with skin (GHS category 5: acutely toxic - dermal).
Toxic to aquatic life with long lasting effects (GHS category 2: aquatic toxicity - acute and/or chronic).

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0.1\%$.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Beadlock Trim - Ceramic Coating

Version number: GHS 2.0
Replaces version of: 2023-10-27 (GHS 1)

Revision: 2024-04-11

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
tert-butyl acetate	CAS No 540-88-5	40 - < 55	Flam. Liq. 2 / H225	
Cyclosilazanes, di-Me, Me Hydrogen, polymers with di-Me, Me hydrogen silazanes, and 2,4-TDI		20 - < 40	Acute Tox. 4 / H302 Skin Corr. 1B / H314 Eye Dam. 1 / H318 Skin Sens. 1 / H317 Flam. Liq. 3 / H226	
cyclic, linear or branched completely methylated siloxanes	CAS No not available	1 - < 5	Flam. Liq. 3 / H226	

Hazardous ingredients, Consideration of other advice

Exact percentage of ingredients is withheld as a trade secret.

Remarks

For full text of abbreviations: see SECTION 16.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Beadlock Trim - Ceramic Coating

Version number: GHS 2.0
Replaces version of: 2023-10-27 (GHS 1)

Revision: 2024-04-11

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Beadlock Trim - Ceramic Coating

Version number: GHS 2.0
Replaces version of: 2023-10-27 (GHS 1)

Revision: 2024-04-11

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Beadlock Trim - Ceramic Coating

Version number: GHS 2.0
Replaces version of: 2023-10-27 (GHS 1)

Revision: 2024-04-11

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	tert-butyl acetate	540-88-5	PEL (CA)	200	950						Cal/ OSHA PEL
US	tert-butyl acetate	540-88-5	REL	200 (10 h)	950 (10 h)						NIOSH REL
US	tert-butyl acetate	540-88-5	TLV®	50		150					AC-GIH® 2019
US	tert-butyl acetate	540-88-5	PEL	200	950						29 CFR 1910.1000

Notation

Ceiling-C
STEL

ceiling value is a limit value above which exposure should not occur

short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs of components

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
tert-butyl acetate	540-88-5	DNEL	159 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
tert-butyl acetate	540-88-5	DNEL	714 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
tert-butyl acetate	540-88-5	DNEL	22 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components

Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
tert-butyl acetate	540-88-5	PNEC	0.016 mg/l	aquatic organisms	freshwater	short-term (single instance)



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Beadlock Trim - Ceramic Coating

Version number: GHS 2.0
Replaces version of: 2023-10-27 (GHS 1)

Revision: 2024-04-11

Relevant PNECs of components						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
tert-butyl acetate	540-88-5	PNEC	0.002 mg/l	aquatic organisms	marine water	short-term (single instance)
tert-butyl acetate	540-88-5	PNEC	0.15 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
tert-butyl acetate	540-88-5	PNEC	0.17 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
tert-butyl acetate	540-88-5	PNEC	0.017 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
tert-butyl acetate	540-88-5	PNEC	0.025 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection. According to EN166 .

Skin protection

- Hand protection

Wear suitable gloves. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Chemical protection gloves (nitrile) which are tested according to EN 374.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Beadlock Trim - Ceramic Coating

Version number: GHS 2.0
Replaces version of: 2023-10-27 (GHS 1)

Revision: 2024-04-11

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	colorless to pale yellow; transparent
Particle	not relevant (liquid)
Odor	characteristic - like ammonia

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	93 °C at 101 kPa
Flash point	9 °C at 101 kPa closed cup
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)
Vapor pressure	42 Torr at 20 °C
Density	8 lb/gal at 25 °C
Vapor density	this information is not available
Relative density	0.96 at 25 °C (water = 1)
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	270 °C (auto-ignition temperature (liquids and gases))
Viscosity	not determined
Explosive properties	none



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Beadlock Trim - Ceramic Coating

Version number: GHS 2.0
Replaces version of: 2023-10-27 (GHS 1)

Revision: 2024-04-11

Oxidizing properties	none
Temperature class (USA, acc. to NEC 500)	T2B (maximum permissible surface temperature on the equipment: 260 °C)

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful in contact with skin.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Beadlock Trim - Ceramic Coating

Version number: GHS 2.0
Replaces version of: 2023-10-27 (GHS 1)

Revision: 2024-04-11

Acute toxicity estimate (ATE) of components

Name of substance	CAS No	Exposure route	ATE
Cyclosilazanes, di-Me, Me Hydrogen, polymers with di-Me, Me hydrogen silazanes, and 2,4-TDI		oral	500 mg/kg

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
tert-butyl acetate	540-88-5	LC50	240 mg/l	fish	96 h
tert-butyl acetate	540-88-5	EC50	410 mg/l	aquatic invertebrates	24 h
tert-butyl acetate	540-88-5	ErC50	64 mg/l	algae	96 h



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Beadlock Trim - Ceramic Coating

Version number: GHS 2.0
Replaces version of: 2023-10-27 (GHS 1)

Revision: 2024-04-11

Aquatic toxicity (chronic) of components

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
tert-butyl acetate	540-88-5	EC50	410 mg/l	aquatic invertebrates	24 h

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Beadlock Trim - Ceramic Coating

Version number: GHS 2.0
Replaces version of: 2023-10-27 (GHS 1)

Revision: 2024-04-11

SECTION 14: Transport information

14.1 UN number

DOT	UN 2924
IMDG-Code	UN 2924
ICAO-TI	UN 2924

14.2 UN proper shipping name

DOT	Flammable liquid, corrosive, n.o.s.
IMDG-Code	FLAMMABLE LIQUID, CORROSIVE, N.O.S.
ICAO-TI	Flammable liquid, corrosive, n.o.s.
Technical name (hazardous ingredients)	Cyclosilazanes, di-Me, Me Hydrogen, polymers with di-Me, Me hydrogen silazanes, and 2,4-TDI, tert-butyl acetate

14.3 Transport hazard class(es)

DOT	3 (8)
IMDG-Code	3 (8)
ICAO-TI	3 (8)

14.4 Packing group

DOT	II
IMDG-Code	II
ICAO-TI	II

14.5 Environmental hazards

	hazardous to the aquatic environment
Environmentally hazardous substance (aquatic environment)	alkyl polysilicates

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Particulars in the shipper's declaration	UN2924, Flammable liquid, corrosive, n.o.s., (contains: Cyclosilazanes, di-Me, Me Hydrogen, polymers with di-Me, Me hydrogen silazanes, and 2,4-TDI, tert-butyl acetate), 3 (8), II, environmentally hazardous
Reportable quantity (RQ)	11,236 lbs (5,101 kg) (tert-butyl acetate)



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Beadlock Trim - Ceramic Coating

Version number: GHS 2.0
Replaces version of: 2023-10-27 (GHS 1)

Revision: 2024-04-11

Danger label(s) 3+8, fish and tree



Environmental hazards YES (hazardous to the aquatic environment)

Special provisions (SP) IB2, T11, TP2, TP27

ERG No 132

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant YES (hazardous to the aquatic environment) (alkyl polysilicates)

Danger label(s) 3+8, fish and tree



Special provisions (SP) 274

Excepted quantities (EQ) E2

Limited quantities (LQ) 1 L

EmS F-E, S-C

Stowage category B

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Environmental hazards YES (hazardous to the aquatic environment)

Danger label(s) 3+8



Special provisions (SP) A3

Excepted quantities (EQ) E2

Limited quantities (LQ) 0,5 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA) not all ingredients are listed (ACTIVE)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

none of the ingredients are listed



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Beadlock Trim - Ceramic Coating

Version number: GHS 2.0
Replaces version of: 2023-10-27 (GHS 1)

Revision: 2024-04-11

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
tert-butyl acetate	540-88-5		1	5000 (2270)

Legend

1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
tert-butyl acetate	540-88-5	solvents	
alkyl polysilicates	Trade Secret	resin	
Cyclosilazanes, di-Me, Me Hydrogen, polymers with di-Me, Me hydrogen silazanes, and 2,4-TDI		refractory resin	
cyclic, linear or branched completely methylated siloxanes	not available	shine agent	
silicone based rheology modifier	not available	viscosity modifier	

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
tert-butyl acetate	540-88-5				1.0 %

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
tert-butyl acetate	540-88-5	A, O	

Legend

A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
 O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Beadlock Trim - Ceramic Coating

Version number: GHS 2.0
Replaces version of: 2023-10-27 (GHS 1)

Revision: 2024-04-11

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
tert-butyl acetate	540-88-5		F3

Legend

F3 Flammable - Third Degree

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
ACETIC ACID, 1,1-DIMETHYLETHYL ESTER	540-88-5	E

Legend

E Environmental hazard

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
tert-butyl acetate	540-88-5	T

Legend

T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

none of the ingredients are listed

VOC content

- Regulated Volatile Organic Compounds (VOC-EPA) 0 %
- Regulated Volatile Organic Compounds (VOC-Cal ARB) 0 %

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	/	none
Health	3	major injury likely unless prompt action is taken and medical treatment is given
Flammability	3	material that can be ignited under almost all ambient temperature conditions
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Beadlock Trim - Ceramic Coating

Version number: GHS 2.0
Replaces version of: 2023-10-27 (GHS 1)

Revision: 2024-04-11

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	3	material that can be ignited under almost all ambient temperature conditions
Health	3	material that, under emergency conditions, can cause serious or permanent injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
CA	DSL	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
US	TSCA	not all ingredients are listed
AU	AIIC	not all ingredients are listed
CN	IECSC	not all ingredients are listed
EU	ECSI	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed
PH	PICCS	not all ingredients are listed
TW	TCSI	not all ingredients are listed
VN	NCI	not all ingredients are listed

Legend

AIIC	Australian Inventory of Industrial Chemicals
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NCI	National Chemical Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Beadlock Trim - Ceramic Coating

Version number: GHS 2.0
Replaces version of: 2023-10-27 (GHS 1)

Revision: 2024-04-11

Legend

TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
1.2		Uses advised against: Do not use for squirting or spraying. Do not use for products which come into direct contact with the skin.	yes
1.3	Details of the supplier of the safety data sheet: Shine Supply 1302 Tower Square, Unit 1 Ventura, CA. 93003 805-535-4332 info@shinesupply.com	Details of the supplier of the safety data sheet: Shine Supply 1343 Callens Rd. Ventura CA 93003 805-535-4332 info@shinesupply.com	yes
2.1		Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200): change in the listing (table)	yes
2.1	The most important adverse physicochemical, human health and environmental effects: The product is combustible and can be ignited by potential ignition sources.	The most important adverse physicochemical, human health and environmental effects: Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis. The product is combustible and can be ignited by potential ignition sources.	yes
2.2		- Pictograms: change in the listing (table)	yes
2.2		- Hazard statements: change in the listing (table)	yes
2.2		- Precautionary statements: change in the listing (table)	yes
2.2		- Hazardous ingredients for labelling: Cyclosilazanes, di-Me, Me Hydrogen, polymers with di-Me, Me hydrogen silazanes, and 2,4-TDI	yes
2.3	Results of PBT and vPvB assessment: Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$.	Results of PBT and vPvB assessment: Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0.1\%$.	yes
3.2		Description of the mixture: change in the listing (table)	yes



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Beadlock Trim - Ceramic Coating

Version number: GHS 2.0
Replaces version of: 2023-10-27 (GHS 1)

Revision: 2024-04-11

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
3.2	Hazardous ingredients, Consideration of other advice: Exact percentage of ingredients is withheld as a trade secret. For full text of abbreviations: see SECTION 16.	Hazardous ingredients, Consideration of other advice: Exact percentage of ingredients is withheld as a trade secret.	yes
3.2		Remarks: For full text of abbreviations: see SECTION 16.	yes
11.1		Acute toxicity estimate (ATE) of components: change in the listing (table)	yes
11.1	Skin corrosion/irritation: Causes skin irritation.	Skin corrosion/irritation: Causes severe skin burns and eye damage.	yes
11.1	Serious eye damage/eye irritation: Shall not be classified as seriously damaging to the eye or eye irritant.	Serious eye damage/eye irritation: Causes serious eye damage.	yes
11.1	Respiratory or skin sensitization: Shall not be classified as a respiratory or skin sensitizer.	Respiratory or skin sensitization: May cause an allergic skin reaction.	yes
14.1	DOT: UN 1993	DOT: UN 2924	yes
14.1	IMDG-Code: UN 1993	IMDG-Code: UN 2924	yes
14.1	ICAO-TI: UN 1993	ICAO-TI: UN 2924	yes
14.2	DOT: Flammable liquid, n.o.s.	DOT: Flammable liquid, corrosive, n.o.s.	yes
14.2	IMDG-Code: FLAMMABLE LIQUID, N.O.S.	IMDG-Code: FLAMMABLE LIQUID, CORROSIVE, N.O.S.	yes
14.2	ICAO-TI: Flammable liquid, n.o.s.	ICAO-TI: Flammable liquid, corrosive, n.o.s.	yes
14.2	Technical name (hazardous ingredients): tert-butyl acetate, Cyclosilazanes, di-Me, Me Hydrogen, polymers with di-Me, Me hydrogen silazanes, and 2,4-TDI	Technical name (hazardous ingredients): Cyclosilazanes, di-Me, Me Hydrogen, polymers with di-Me, Me hydrogen silazanes, and 2,4-TDI, tert-butyl acetate	yes
14.3	DOT: 3	DOT: 3 (8)	yes
14.3	IMDG-Code: 3	IMDG-Code: 3 (8)	yes
14.3	ICAO-TI: 3	ICAO-TI: 3 (8)	yes
14.7	Particulars in the shipper's declaration: UN1993, Flammable liquid, n.o.s., (contains: tert-butyl acetate, Cyclosilazanes, di-Me, Me Hydrogen, polymers with di-Me, Me hydrogen silazanes, and 2,4-TDI), 3, II, environmentally hazardous	Particulars in the shipper's declaration: UN2924, Flammable liquid, corrosive, n.o.s., (contains: Cyclosilazanes, di-Me, Me Hydrogen, polymers with di-Me, Me hydrogen silazanes, and 2,4-TDI, tert-butyl acetate), 3 (8), II, environmentally hazardous	yes



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Beadlock Trim - Ceramic Coating

Version number: GHS 2.0
Replaces version of: 2023-10-27 (GHS 1)

Revision: 2024-04-11

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
14.7	Danger label(s): 3, fish and tree	Danger label(s): 3+8, fish and tree	yes
14.7		Danger label(s): change in the listing (table)	yes
14.7	Special provisions (SP): IB2, T7, TP1, TP8, TP28	Special provisions (SP): IB2, T11, TP2, TP27	yes
14.7	ERG No: 128	ERG No: 132	yes
14.7	Danger label(s): 3, fish and tree	Danger label(s): 3+8, fish and tree	yes
14.7		Danger label(s): change in the listing (table)	yes
14.7	EmS: F-E, <u>S-E</u>	EmS: F-E, S-C	yes
14.7	Danger label(s): 3	Danger label(s): 3+8	yes
14.7		Danger label(s): change in the listing (table)	yes
14.7	Limited quantities (LQ): 1 L	Limited quantities (LQ): 0,5 L	yes
15.1		Cleaning Product Right to Know Act Substance List (CA-RTK): change in the listing (table)	yes
15.1		NPCA-HMIS® III: change in the listing (table)	yes
15.1		NFPA® 704: change in the listing (table)	yes
16		Abbreviations and acronyms: change in the listing (table)	yes
16		List of relevant phrases (code and full text as stated in section 2 and 3): change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Beadlock Trim - Ceramic Coating

Version number: GHS 2.0
Replaces version of: 2023-10-27 (GHS 1)

Revision: 2024-04-11

Abbr.	Descriptions of used abbreviations
ACGIH® 2019	From ACGIH®, 2019 TLVs® and BEIs® Book. Copyright 2019. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Cal ARB	California Air Resources Board
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
EPA	Environmental Protection Agency. An agency of the federal government of the United States charged with protecting human health and the environment
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
ERG No	Emergency Response Guidebook - Number
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Beadlock Trim - Ceramic Coating

Version number: GHS 2.0
Replaces version of: 2023-10-27 (GHS 1)

Revision: 2024-04-11

Abbr.	Descriptions of used abbreviations
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LHS	Lower hazard substance
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitization
STEL	Short-term exposure limit
TLV®	Threshold Limit Values
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Beadlock Trim - Ceramic Coating

Version number: GHS 2.0
Replaces version of: 2023-10-27 (GHS 1)

Revision: 2024-04-11

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.