SHINE \* SUPPLY \*

acc. to 29 CFR 1910.1200 App D

# **Shine Supply Classic Finish**

Version number: GHS 3.0 Revision: 2024-04-09 Replaces version of: 2022-03-03 (GHS 2)

### **SECTION 1: Identification**

### 1.1 Product identifier

Trade name Shine Supply Classic Finish

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Vehicle polishing compound

Professional use Industrial use

### 1.3 Details of the supplier of the safety data sheet

Shine Supply 1343 Callens Rd. Ventura CA 93003

805-535-4332 info@shinesupply.com

### 1.4 Emergency telephone number

Emergency information service

USA 1.800.535.5053, INTL 1.352.323.3500 24 hour emergency number

### **SECTION 2: Hazard(s) identification**

#### 2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and cat- egory	Hazard state- ment
A.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
B.6	flammable liquid	4	Flam. Liq. 4	H227

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects
The product is combustible and can be ignited by potential ignition sources.

### 2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word warning

- Pictograms

GHS07



United States: en Page: 1 / 18



acc. to 29 CFR 1910.1200 App D

# **Shine Supply Classic Finish**

Version number: GHS 3.0 Revision: 2024-04-09 Replaces version of: 2022-03-03 (GHS 2)

- Hazard statements

H227 Combustible liquid.
H315 Causes skin irritation.

- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 If on skin: Wash with plenty of water.
P321 Specific treatment (see on this label).

P332+P313 If skin irritation occurs: Get medical advice/attention.
P362 Take off contaminated clothing and wash before reuse.

P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### 2.3 Other hazards

This material is combustible, but will not ignite readily.

Hazards not otherwise classified

Harmful to aquatic life with long lasting effects (GHS category 3: aquatic toxicity - acute and/or chronic).

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of  $\geq$  0.1%.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of  $\geq$  0.1%.

### **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

Not relevant (mixture)

#### 3.2 Mixtures

#### Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
naphthenic oil, severely hydro- treated	CAS No 64741-86-2	12-<20	Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Asp. Tox. 1 / H304	
distillates (petroleum) hydro- treated, light	CAS No 64742-47-8	5-<12	Asp. Tox. 1 / H304	
odorless mineral spirits	CAS No 64742-48-9	1-<5	Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	
White mineral oil (petroleum)	CAS No 8042-47-5	1-<5	Asp. Tox. 1 / H304	

United States: en Page: 2 / 18

SHINE \* SUPPLY \*

acc. to 29 CFR 1910.1200 App D

# **Shine Supply Classic Finish**

Version number: GHS 3.0 Revision: 2024-04-09 Replaces version of: 2022-03-03 (GHS 2)

Hazardous ingredients, Consideration of other advice

Exact percentage of ingredients is withheld as a trade secret.

#### Remarks

For full text of abbreviations: see SECTION 16.

### **SECTION 4: First-aid measures**

### 4.1 Description of first-aid measures

#### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

#### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

#### Following skin contact

Wash with plenty of soap and water.

#### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

#### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

### 4.3 Indication of any immediate medical attention and special treatment needed

none

### **SECTION 5: Fire-fighting measures**

### 5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO2)

Unsuitable extinguishing media

Water jet

### 5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

United States: en Page: 3 / 18



acc. to 29 CFR 1910.1200 App D

# **Shine Supply Classic Finish**

Version number: GHS 3.0 Revision: 2024-04-09 Replaces version of: 2022-03-03 (GHS 2)

### Hazardous combustion products

Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO2)

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow fire-fighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

#### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

### 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

### **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

United States: en Page: 4 / 18

SHINE \* SUPPLY \*

acc. to 29 CFR 1910.1200 App D

### **Shine Supply Classic Finish**

Version number: GHS 3.0 Revision: 2024-04-09 Replaces version of: 2022-03-03 (GHS 2)

#### - Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air.

### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

#### Control of the effects

Protect against external exposure, such as

frost

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

#### 7.3 Specific end use(s)

See section 16 for a general overview.

#### **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### Occupational exposure limit values (Workplace Exposure Limits)

Coun try	Name of agent	CAS No	Iden- tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m³]	Nota- tion	Sourc e
US	alpha-Alumina	1344-28- 1	REL							appx- D	NIOSH REL
US	alpha-alumina	1344-28- 1	PEL		15					i, dust	29 CFR 1910.1 000
US	alpha-alumina	1344-28- 1	PEL		5					r, dust	29 CFR 1910.1 000

United States: en Page: 5 / 18



acc. to 29 CFR 1910.1200 App D

# **Shine Supply Classic Finish**

Version number: GHS 3.0 Revision: 2024-04-09 Replaces version of: 2022-03-03 (GHS 2)

### Occupational exposure limit values (Workplace Exposure Limits)

Coun try	Name of agent	CAS No	Iden- tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m³]	Nota- tion	Sourc e
US	aluminium, insol- uble compounds	1344-28- 1	TLV®		1					r	AC- GIH® 2019
US	aluminium oxide	1344-28- 1	PEL (CA)		10					dust	Cal/ OSHA PEL
US	aluminium oxide	1344-28- 1	PEL (CA)		5					r	Cal/ OSHA PEL
US	petroleum distil- lates (naphtha) (rubber solvent)	64742- 48-9	PEL	500	2,000						29 CFR 1910.1 000
US	mineral oil	8042-47- 5	TLV®		5					i, ex- Met- Work- Fl	AC- GIH® 2019

Notation

appx-D see Appendix D - Substances with No Established RELs

Ceiling-C ceiling value is a limit value above which exposure should not occur

dust as dust

exMetWorkFl excluding metal working fluids

i inhalable fraction respirable fraction

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless other-

wise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average.

age (unless otherwise specified

### Relevant DNELs of components

Name of sub- stance	CAS No	End- point	Threshold level	Protection goal, route of expos- ure	Used in	Exposure time
White mineral oil (pet- roleum)	8042-47-5	DNEL	165 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic ef- fects
White mineral oil (pet- roleum)	8042-47-5	DNEL	217 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

### 8.2 Exposure controls

Appropriate engineering controls

General ventilation.

United States: en Page: 6 / 18

SHINE \* SUPPLY \*

acc. to 29 CFR 1910.1200 App D

# **Shine Supply Classic Finish**

Version number: GHS 3.0 Revision: 2024-04-09 Replaces version of: 2022-03-03 (GHS 2)

Individual protection measures (personal protective equipment)

### Eye/face protection

Wear eye/face protection. According to EN166 .

### Skin protection

#### - Hand protection

Wear suitable gloves. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Chemical protection gloves (nitrile) which are tested according to EN 374.

#### - Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

#### Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

#### **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

#### **Appearance**

Physical state	liquid
Color	grey
Particle	not relevant (liquid)
Odor	characteristic

### Other safety parameters

pH (value)	8-8.6 (25 °C)
Melting point/freezing point	not determined
Initial boiling point and boiling range	100 °C
Flash point	65 °C at 101 kPa 149 °F at 760 mmHg closed cup
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)

United States: en Page: 7 / 18



acc. to 29 CFR 1910.1200 App D

# **Shine Supply Classic Finish**

Version number: GHS 3.0 Revision: 2024-04-09 Replaces version of: 2022-03-03 (GHS 2)

#### **Explosive limits**

- Lower explosion limit (LEL)	0.6 vol%
- Upper explosion limit (UEL)	5 vol%
Vapor pressure	32 hPa at 25 °C
Density	0.98 – 1 <sup>g</sup> / <sub>ml</sub>
Vapor density	this information is not available
Solubility(ies)	not determined

### Partition coefficient

- n-octanol/water (log KOW)	this information is not available		
Auto-ignition temperature	225 °C (auto-ignition temperature (liquids and gases))		

### Viscosity

- Kinematic viscosity	5,000 cSt
- Dynamic viscosity	5,005 cP
Explosive properties	none
Oxidizing properties	none
Temperature class (USA, acc. to NEC 500)	T2D (maximum permissible surface temperature on the equipment: 215°C)

# **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

### 10.2 Chemical stability

See below "Conditions to avoid".

### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

United States: en Page: 8 / 18



acc. to 29 CFR 1910.1200 App D

# **Shine Supply Classic Finish**

Version number: GHS 3.0 Revision: 2024-04-09 Replaces version of: 2022-03-03 (GHS 2)

### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

### 10.5 Incompatible materials

Oxidizers

### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

### **SECTION 11: Toxicological information**

### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate	(ATE) o	f components	

Name of substance	CAS No	Exposure route	ATE
naphthenic oil, severely hydrotreated	64741-86-2	inhalation: vapor	11 <sup>mg</sup> / <sub>l</sub> /4h
naphthenic oil, severely hydrotreated	64741-86-2	inhalation: dust/mist	1.8 <sup>mg</sup> / <sub>l</sub> /4h
White mineral oil (petroleum)	8042-47-5	inhalation: dust/mist	>5 <sup>mg</sup> / <sub>l</sub> /4h

### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

#### Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

### Carcinogenicity

Shall not be classified as carcinogenic.

United States: en Page: 9 / 18

SHINE \* SUPPLY \*

acc. to 29 CFR 1910.1200 App D

# **Shine Supply Classic Finish**

Version number: GHS 3.0 Revision: 2024-04-09 Replaces version of: 2022-03-03 (GHS 2)

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

### **SECTION 12: Ecological information**

### 12.1 Toxicity

Harmful to aquatic life with long lasting effects.

### Aquatic toxicity (acute) of components

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
naphthenic oil, severely hydrotreated	64741-86-2	LL50	180 <sup>mg</sup> / <sub>l</sub>	fish	48 h
naphthenic oil, severely hydrotreated	64741-86-2	EL50	210 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	48 h
odorless mineral spirits	64742-48-9	LL50	8.2 <sup>mg</sup> / <sub>I</sub>	fish	96 h
odorless mineral spirits	64742-48-9	EL50	4.5 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	48 h
White mineral oil (petro- leum)	8042-47-5	LL50	>10,000 <sup>mg</sup> / <sub>I</sub>	fish	96 h

### Aquatic toxicity (chronic) of components

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
naphthenic oil, severely hydrotreated	64741-86-2	LL50	>1,000 <sup>mg</sup> / <sub>I</sub>	fish	24 h
naphthenic oil, severely hydrotreated	64741-86-2	EL50	>1,000 <sup>mg</sup> / <sub>I</sub>	aquatic invertebrates	24 h
odorless mineral spirits	64742-48-9	EL50	10 <sup>mg</sup> / <sub>l</sub>	fish	21 d
odorless mineral spirits	64742-48-9	EC50	15 <sup>mg</sup> / <sub>I</sub>	microorganisms	40 h

### 12.2 Persistence and degradability

Data are not available.

United States: en Page: 10 / 18

SHINE \* SUPPLY \*

acc. to 29 CFR 1910.1200 App D

# **Shine Supply Classic Finish**

Version number: GHS 3.0 Revision: 2024-04-09 Replaces version of: 2022-03-03 (GHS 2)

### 12.3 Bioaccumulative potential

Data are not available.

### 12.4 Mobility in soil

Data are not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of  $\geq 0.1\%$ .

#### 12.7 Other adverse effects

Data are not available.

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

### **SECTION 14: Transport information**

**14.1 UN number** not subject to transport regulations

**14.2 UN proper shipping name** not relevant

14.3 Transport hazard class(es) none

14.4 Packing group not assigned

**14.5 Environmental hazards** non-environmentally hazardous acc. to the dangerous

goods regulations

#### 14.6 Special precautions for user

There is no additional information.

### 14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

United States: en Page: 11 / 18



acc. to 29 CFR 1910.1200 App D

# **Shine Supply Classic Finish**

Revision: 2024-04-09

Version number: GHS 3.0
Replaces version of: 2022-03-03 (GHS 2)

### Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information Not subject to transport regulations.

International Maritime Dangerous Goods Code (IMDG) - Additional information Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information Not subject to ICAO-IATA.

### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations specific for the product in question National regulations (United States)

Superfund Amendment and Reauthorization Act (SARA TITLE III )

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

### **Clean Air Act**

none of the ingredients are listed

### **Right to Know Hazardous Substance List**

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
water	7732-18-5	solvent	
naphthenic oil, severely hydrotreated	64741-86-2	solvents	EC Annex VI CMRs - Cat. 1B
aluminium oxide	1344-28-1	abrasive	
distillates (petroleum) hydrotreated, light	64742-47-8	solvents	
odorless mineral spirits	64742-48-9	solvents	Canada PBiTs EC Annex VI CMRs - Cat. 1B
White mineral oil (petroleum)	8042-47-5	lubricant	
acrylic polymer	75760-37-1	viscosity modifier	
triethanolamine	102-71-6	pH adjusting agent	
Alcohols,C8-10,ethoxylatedpropoxylated	68603-25-8	surfactant	
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	solvents	EC Annex VI CMRs - Cat. 1B
Tetrasodium EDTA, anhydrous	64-02-8	chelate / se- questrant	

United States: en Page: 12 / 18





# **Shine Supply Classic Finish**

Version number: GHS 3.0 Revision: 2024-04-09 Replaces version of: 2022-03-03 (GHS 2)

Name of substance	CAS No	Functionality	Authoritative Lists
2-methylpentane-2,4-diol	107-41-5	humectant	

### - Hazardous Substances List (MN-ERTK)

	Name of substance	CAS No	References	Remarks
- 1	odorless mineral spirits	64742-48-9	A, O	

### Legend

A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH

O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, sub-part Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

# California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals					
Name of substance	Name acc. to inventory	CAS No	Wt%	Remarks	Type of the tox-icity
C.I. Pigment Black 7	carbon black	1333-86-4	0.004	airborne, un- bound particles of respirable size	cancer
2,2'-iminodiethanol	diethanolamine	111-42-2	0.0015		cancer

### **VOC** content

- Regulated Volatile Organic Compounds (VOC-EPA) 4 %

- Regulated Volatile Organic Compounds (VOC-Cal ARB) 4 %

# Industry or sector specific available guidance(s)

### **NPCA-HMIS® III**

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

United States: en Page: 13 / 18

acc. to 29 CFR 1910.1200 App D

# **Shine Supply Classic Finish**

Revision: 2024-04-09 Version number: GHS 3.0 Replaces version of: 2022-03-03 (GHS 2)

### **NFPA® 704**

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

#### **National inventories**

Country	Inventory	Status
EU	REACH Reg.	not all ingredients are listed
CA	DSL	all ingredients are listed
US	TSCA	all ingredients are listed (ACTIVE)
AU	AIIC	not all ingredients are listed
CN	IECSC	not all ingredients are listed
EU	ECSI	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed
PH	PICCS	not all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed

Legend

AIIC Australian Inventory of Industrial Chemicals CICR Chemical Inventory and Control Regulation

**CSCL-ENCS** List of Existing and New Chemical Substances (CSCL-ENCS)

DSL

Domestic Substances List (DSL) EC Substance Inventory (EINECS, ELINCS, NLP) **ECSI** 

Inventory of Existing Chemical Substances Produced or Imported in China National Inventory of Chemical Substances **IECSC** 

INSQ

ISHA-ENCS Inventory of Existing and New Chemical Substances (ISHA-ENCS)

KECI Korea Existing Chemicals Inventory NZIoC New Zealand Inventory of Chemicals

**PICCS** Philippine Inventory of Chemicals and Chemical Substances (PICCS)

United States: en Page: 14 / 18

acc. to 29 CFR 1910.1200 App D

# **Shine Supply Classic Finish**

Version number: GHS 3.0 Revision: 2024-04-09 Replaces version of: 2022-03-03 (GHS 2)

Legend

REACH Reg.
TCSI
TSCA
REACH registered substances
Taiwan Chemical Substance Inventory
Toxic Substance Control Act

### 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information, including date of preparation or last revision

### Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relevant
1.2	Relevant identified uses: Vehicle polishing compound	Relevant identified uses: Vehicle polishing compound Professional use Industrial use	yes
1.3	Details of the supplier of the safety data sheet: Shine Supply 1302 Tower Square, Unit 1 Ventura, CA. 93003 805-535-4332 info@shinesupply.com	Details of the supplier of the safety data sheet: Shine Supply 1343 Callens Rd. Ventura CA 93003  805-535-4332 info@shinesupply.com	yes
1.4	Emergency information service: Nødtelefon: Telefon +47 22 59 13 00 Beskrivelse: Giftinformasjonen	Emergency information service: USA 1.800.535.5053, INTL 1.352.323.3500 24 hour emergency number	yes
2.2		- Precautionary statements: change in the listing (table)	yes
2.3		Hazards not otherwise classified: change in the listing (table)	yes
2.3		Results of PBT and vPvB assessment:  Does not contain a PBT-/vPvB-substance at a concentration of ≥ 0.1%.	yes
2.3		Endocrine disrupting properties:  Does not contain an endocrine disruptor (ED) in a concentration of ≥ 0.1%.	yes
3.2		Description of the mixture: change in the listing (table)	yes
3.2	Hazardous ingredients, Consideration of other advice: Exact percentage of ingredients is withheld as a trade secret.For full text of abbreviations: see SECTION 16.	Hazardous ingredients, Consideration of other advice: Exact percentage of ingredients is withheld as a trade secret.	yes
3.2		Remarks: For full text of abbreviations: see SECTION 16.	yes

United States: en Page: 15 / 18





# **Shine Supply Classic Finish**

Version number: GHS 3.0
Replaces version of: 2022-03-03 (GHS 2)
Revision: 2024-04-09

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relevant
6.2	Environmental precautions: Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.	Environmental precautions: Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.	yes
11.1	Acute toxicity: Shall not be classified as acutely toxic.GHS of the United Nations, annex 4: May be harmful if inhaled.	Acute toxicity: Shall not be classified as acutely toxic.	yes
11.1		Acute toxicity estimate (ATE) of components: change in the listing (table)	yes
12.1		Aquatic toxicity (acute) of components: change in the listing (table)	yes
12.1		Aquatic toxicity (chronic) of components: change in the listing (table)	yes
12.6	Endocrine disrupting properties: None of the ingredients are listed.	Endocrine disrupting properties:  Does not contain an endocrine disruptor (ED) in a concentration of ≥ 0.1%.	yes
14.3	Transport hazard class(es): not assigned	Transport hazard class(es): none	yes
15.1	Toxic Substance Control Act (TSCA): all ingredients are listed		yes
15.1		Cleaning Product Right to Know Act Substance List (CA-RTK): change in the listing (table)	yes
15.1		National inventories: change in the listing (table)	yes
16		Abbreviations and acronyms: change in the listing (table)	yes
16		List of relevant phrases (code and full text as stated in section 2 and 3): change in the listing (table)	yes

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH® 2019	From ACGIH®, 2019 TLVs® and BEIs® Book. Copyright 2019. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Acute Tox.	Acute toxicity

United States: en Page: 16 / 18



acc. to 29 CFR 1910.1200 App D

# **Shine Supply Classic Finish**

Version number: GHS 3.0 Revision: 2024-04-09 Replaces version of: 2022-03-03 (GHS 2)

s version of: 2022-03-03 (GHS 2)		
Abbr.	Descriptions of used abbreviations	
Asp. Tox.	Aspiration hazard	
ATE	Acute Toxicity Estimate	
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)	
Cal ARB	California Air Resources Board	
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)	
Ceiling-C	Ceiling value	
DGR	Dangerous Goods Regulations (see IATA/DGR)	
DNEL	Derived No-Effect Level	
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval	
ED	Endocrine disruptor	
EINECS	European Inventory of Existing Commercial Chemical Substances	
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms	
ELINCS	European List of Notified Chemical Substances	
EPA	Environmental Protection Agency. An agency of the federal government of the United States charged with protecting human health and the environment	
Flam. Liq.	Flammable liquid	
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations	
IATA	International Air Transport Association	
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)	
ICAO	International Civil Aviation Organization	
IMDG	International Maritime Dangerous Goods Code	
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality	
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)	
NLP	No-Longer Polymer	
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition	
OSHA	Occupational Safety and Health Administration (United States)	
PBT	Persistent, Bioaccumulative and Toxic	
PEL	Permissible exposure limit	
ppm	Parts per million	
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)	

United States: en Page: 17 / 18

SHINE \* SUPPLY \*

acc. to 29 CFR 1910.1200 App D

# **Shine Supply Classic Finish**

Version number: GHS 3.0 Revision: 2024-04-09 Replaces version of: 2022-03-03 (GHS 2)

Abbr.	Descriptions of used abbreviations
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TLV®	Threshold Limit Values
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

### Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

#### **Classification procedure**

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H226	Flammable liquid and vapor.
H227	Combustible liquid.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.

#### **Disclaimer**

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United States: en Page: 18 / 18