

# MSA Temporary Horizontal Lifelines

## Technical Data Sheet



<b>PART NUMBER</b>	<b>10219297</b>
<b>DESCRIPTION</b>	MSA Cable Temporary Horizontal Lifeline, 60 ft. (18 m)
<b>ANCHOR STRAPS INCLUDED</b>	No
<b>LIFELINE LENGTH</b>	5-60 ft. (1.5-18.3 m)
<b>LIFELINE CONSTRUCTION</b>	6 x 19, 5/16 in. (8 mm), fiber core
<b>LIFELINE MATERIAL</b>	Galvanized Steel Cable
<b>CAPACITY</b>	130-310 lb. (59-141 kg)
<b>INSTALL TYPE</b>	Temporary/Portable
<b>TURNBUCKLE</b>	Zinc plated Carbon Steel
<b>THREADED SHAFTS</b>	Stainless Steel, PTFE Coating
<b>ENERGY ABSORBER COVER</b>	Polycarbonate with overmolded rubber
<b>CARABINERS</b>	Triple lock aluminum 30 kN minimum breaking strength
<b>USERS</b>	Max 2 users*
<b>SPAN TYPE</b>	Single span only
<b>PHYSICAL WEIGHT</b>	17.4 lb. (7.9 kg)
<b>RFID</b>	Yes
<b>COMPATIBILITY</b>	MSA Cable Temporary Horizontal Lifeline System is designed for use with compatible MSA components, connectors, and subsystems.
<b>STANDARDS</b>	OSHA 29 CFR 1910.140 / 1926.502

*Each standard has a different capacity*