

# Leakage Prevention Device (LPD)



## Features

- Prevents dripping through micro sprinkles & Foggers during inverted installation.
- Keeps line full of water, enables immediate function during pump start-up.
- It allows all micro sprinklers & Foggers to start / stop simultaneously.

## Low Pressure Leakage Prevention Device (LP-LPD)

Connection compatible with Aquamic inverted models




LPD Operating Pressures	
Black Cap	
Opening	1.1 kg/cm <sup>2</sup>
Closing	0.7 kg/cm <sup>2</sup>

LPD Connection	Male Bayonet x Female Bayonet
----------------	-------------------------------

## Medium Pressure Leakage Prevention Device (MP-LPD)

Connection compatible with Fogger Model




LPD Operating Pressures		
	Green Cap	Blue Cap
Opening	2.0 kg/cm <sup>2</sup>	2.5 kg/cm <sup>2</sup>
Closing	1.1 kg/cm <sup>2</sup>	1.5 kg/cm <sup>2</sup>

LPD Connection	Pushfit Male x Pushfit Female	Pushfit Male x Bayonet Female
----------------	-------------------------------	-------------------------------

## High Pressure Leakage Prevention Device (HP-LPD)

Connection compatible with Fogger Model



LPD Operating Pressures	
Grey Cap	
Opening	3 kg/cm <sup>2</sup>
Closing	2 kg/cm <sup>2</sup>

LPD Connection	Pushfit Male x Pushfit Female	Pushfit Male x Bayonet Female
----------------	-------------------------------	-------------------------------