Liberty 100

Single phase single element electricity meter with intimate modular communications hub

Installation efficiency



Remote

Smart, flexible and future proof

Secure Meters has developed Liberty 100 single phase smart electricity meter to meet UK smart metering requirements. Liberty 100 has modular architecture for both WAN/HAN enabling multiple communications options to be deployed. The modules can be replaced in the field so that investment in the meter is protected even if communications technology needs to be changed during the life of the meter. The communications module acts as hub for communication to head end system and to the gas meter/in home display. The meter and communications hub are capable of remote firmware upgrade after installation to allow features and functionality to be changed. Liberty 100 supports both credit and Pay As You Go (PAYG) modes of operation.

Application

- · Smart electricity meter with communication hub for dual fuel (electricity + gas) and single fuel (electricity) domestic customers in both credit and PAYG modes
- · Metering for small commercial premises including credit and PAYG modes
- Import and export metering for local generation

Benefits

- · Modular communication module allows multiple WAN and HAN options for different communications providers
- Simple installation, registration and pairing process
- Remotely switchable between credit and PAYG modes
- Assists consumers in reducing energy consumption



Features

- Meets requirements of SMETS1 and SSWG
- Four-guadrant measurement with import/export registration
- Time of use/complex tariffs and maximum demand
- Logging of multi parameter load survey, billing data, events including power outage and abnormalities
- Integrated contactor
- Multiple WAN communication options GPRS, long range radio
- Liberty 100 communication hub acts as coordinator for Zigbee HAN and mirror for gas meter data
- Credit and PAYG modes (meter maintains account and tariffs)
- Keypad to enable local entry of Pay as You Go token if WAN not available
- Remote firmware upgrade (not metrology)



Technical specifications

Electrical	
Connection type	Direct connected
Wiring configuration	Single phase, two wire
Voltage range	230 Vac (nom)
Current range	0.5-20 (100) A
Accuracy	Active energy MID class B, reactive energy class 2.0
Mains frequency	50 Hz ± 5%
Burden	Compliant with relevant standard
Compliance	
Standards	MID class B EN 50470-1,3; IEC62053-23
Mechanical	
Modular design	Field replaceable communication module
Dimensions (W x H x D)	140 x 175 x 60 mm
Terminals	Tunnel type with 2 screws compliant to Bs7856
Weight	1 kg (approx.)
Enclosure	Flame retardant polycarbonate
Environmental	
Ingress protection	IP 54
Insulation class	Protective class II
Temperature	-25 °C to +55°C (operating), -25 °C to +70 °C (storage)
Humidity	95% non-condensing
Features	
Firmware	Remote firmware upgrade with rollback
Tariff	Time of use (TOU) and complex (slab within TOU) supported
	Pending tariff structures supported
Load survey	13 months, 4 channels
Display	Backlit 10-character alphanumeric starburst display with icons for status
Keypad	12 way - 0-9, A, B for local entry of PAYG code and access to displays
PAYG functionality	Credit and PAYG modes (meter maintains account and tariffs)
	Display of current and historical consumption with cost of consumption data
	Emergency credit with optional load limiting
	Friendly credit (avoids disconnection during unsocial hours or weekends)
Converter	Debt recovery
Security	AES128 encryption
Tamper detection	Removal of terminal cover, main meter cover, communications hub Excessive magnetic field
Communication	
Local diagnostic port	Optical 1107 hardware-compatible port
Communication module options	GPRS WAN + ZigBee HAN (SEP 1.x)
	Multi operator (roaming) SIMs supported

JSG Metering Solutions LTD

Unit 11, Totman Close, Brook Road Industrial Estate, Rayleigh, Essex, SS6 7UZ

Telephone: 01268 773766 - www.jsgsolutions.co.uk - sales@jsgsolutions.co.uk