

AGROLUBE 10W30 UTTO



AGROLUBE 10W30 UTTO is a special quality lubricant for gearboxes, differentials, hydraulic systems and wet brakes. It is also recommended for lubrication of last generation CVT transmissions.

- ❖ Special lubricant for applications where a UTTO type product is required
- ❖ Hydraulic circuits
- ❖ Transmissions of agricultural and public works machinery
- ❖ Torque converters. Wet brakes

Recommended for machinery JOHN DEERE - MASSEY FERGUSON - FORD - INTERNATIONAL HARVESTER CASE - SAME - FIAT AGRI - DEUTZ...

PACKAGE: 1000l / 200l / 50l / 20l / 5l

VISCOSITY AT 100 °C: 9,3 cSt

VISCOSITY AT 40 °C: 55 cSt

VISCOSITY INDEX (mín.): 152

POUR POINT: -33 °C

FLASH POINT: 240 °C

DENSITY AT 20 °C: 0,865 gr/cm³

COLOUR: Clear yellow

MEETS THE STANDARDS: API GL-4; FORD M2C134D; JOHN DEERE JD20C/JD20D; NEW HOLLAND 3505,3509,3525, FNHA-2-C-200.00, FNHA 2C-201.00; MASSEY FERGUSON 1135, 1138, 1141, 1143, 1145; AGCO Powerfluid 821XL.; ALLISON C4; CAT TO2; ZF TE ML 03E, 05F, 06F, 06K; MAT-3540.

REV.06/20

