

COMPAÑIA GENERAL DE LUBRICANTES SA

C/ Comercio, 36 – Polígono Industrial Can Sunyer 08740 SANT ANDREU DE LA BARCA (Barcelona) Tel.: +34 93 6821514 – Fax: +34 93 6820055 e-mail: gro @cogelsa.com

TECHNICAL DATA SHEET

AGROLUBE 10W30 UTTO ULTRA+

AGROLUBE 10W30 UTTO ULTRA+ is a special quality lubricant for the gearboxes, differentials, hydraulic systems and oil-immersed brakes of tractors, agricultural machinery and public works equipment. It has been especially developed to solve the noise and vibration problem in oil-immersed brakes. It is also recommended for lubrication of the CVT transmission of the latest generation.

- Extreme pressure properties adapted to loaded gears.
- High anti-wear power.
- Special friction properties for oil-immersed brakes and clutches.
- Very high viscosity index.
- Resistance to rust and corrosion.
- Anti-foam, anti-rust.
- Excellent compatibility with gaskets.
- Very low freezing point.
- Correct fluidity that allows improved performance of the hydraulic circuit at low temperature.
- Excellent operation of oil-immersed brakes and clutches, thereby achieving:
 - Braking efficiency
 - Delayed wear of disks
- Reduced wear of gears and of elements of the hydraulic system.
- Effective protection during periods of inactivity.
- Simplified lubrication.

SAE	10W30
VISCOSITY AT 40° C, cSt,(ASTM D-445)	55
VISCOSITY AT 100° C, cSt, (ASTM D-445)	9,3
VISCOSITY INDEX (ASTM D-2270)	152
FREEZING POINT, ° C, (ASTM D-97)	-30

Meets the requirements of: JOHN DEERE J-20 C/D, CASE MS 1210, FORD M2C 86 B/C–M2C 134 D, AGCO POWERFLUID 821XL, API GL-4, CATERPILLAR TO-2, ZF TE-ML 03E-05F-06K-17E-21F, KUBOTA UDT FLUID, MASSEY FERGUSON M 1135 - M 1141- M 1143 - M 1145, ALLISON C-4, CATERPILLAR TO-2, VOLVO WB 101, KUBOTA UDT FLUID, CNH MAT 3505-3509-3525-3540, Fendt, FNHA-2-C-200.00, FNHA-2-C-201.00; CASE MS1210

Revision: 11/19

