



**COMPAÑIA GENERAL DE LUBRICANTES SA**

C/ Comercio, 36 – Polígono Industrial Can Sunyer  
08740 SANT ANDREU DE LA BARCA ( Barcelona )  
Telf: +34 93 6821514 – Fax: +34 93 6820055  
e-mail: gro@cogelsa.com

**TECHNICAL DATA SHEET**

**AGROLUBE STOU 15W40**

**GLOBAL RACING OIL AGROLUBE STOU 15W40** is a multifunctional lubricant specially adapted for the toughest exigencies of the modern agricultural equipment.

Specially designed to lubricate: **ENGINES** on gasoline or diesel, atmospheric or oversupplied. **TRANSMISSIONS**: total protection, for gearboxes, hypoid axels, reductors and all the mechanic transmission parts. **WET BRAKES**: friction properties adapted to all kinds of braking systems. **HYDRAULIC**: properties, antioxidant, antirust and antifoaming, against corrosion, neutral for pentru hoops and hydraulic circuit reserves.

**According to the exigencies:** JOHN DEERE J20C-JDNJ27- MF M-1139-DB 227.1, MAN 271, MACK EO K2, FORD M2C, DEUTZ-FAHR

**Meets:**

ACEA E3  
MB 227,1  
FORD M2C686B/M2C686C/M2C134D/M2C159B/M2C159C  
JOHN DEERE JD20C/JD20D/JD27  
CASE MS1204/MS1206/MS1207/MS1209  
NEW HOLLAND 3525/3526/82009202/82009203  
MASSEY-FERGUSON 1135/1139/1143/1144/1145  
ALLISON C4

API CG4/SF/GL4  
CATERPILLAR TO-2

VISCOSITY AT 40°C, cSt,(ASTM D-445)	100
VISCOSITY AT 100°C, cSt, (ASTM D-445)	14
INDEX OF VISCOSITY (ASTM D-2270)	135
FLASH POINT, °C (ASTM D-92)	232
POUR POINT, °C, (ASTM D-97)	-27
TBN (ASTM D 2896)	11

REV: 02/17

Assessment with respect to the elaboration and utilization of “plannings” for the control and conservation of plants and industrial equipment. COMPAÑIA GENERAL DE LUBRICANTES S.A. is not accountable for the legal actions arised from the inadequate use of the product or products, herein referred to, being, according to our criteria, correct and complying with the quoted DESCRIPTIONS and APPLICATIONS contained herein.

**COMPANY CERTIFIED**

