



COMPANÍA GENERAL DE LUBRICANTES SA

C/ Comercio, 36 – Polígono Industrial Can Sunyer
08740 SANT ANDREU DE LA BARCA (Barcelona)
Telf: +34 93 6821514 – Fax: +34 93 6820055
e-mail: gro@cogelsa.com

TECHNICAL DATA SHEET

BRAKE FLUID DOT 5.1

GLOBAL RACING OIL BRAKE FLUID DOT 5.1 is a 100% synthetic brake fluid for clutches and hydraulic braking systems for light and heavy vehicles, motorcycles and some next-generation bicycles.

It is especially recommended for vehicles with ABS. Its high fluidity at low temperatures guarantees rapid circulation to the stability control systems and improves response time. It is characterized by:

- ❖ HIGH BOILING POINT
- ❖ EXCELLENT THERMAL STABILITY
- ❖ ADDITIVE THAT AVOIDS THE FORMATION OF FOAMS
- ❖ HIGH ANTI-WEAR, ANTI-CORROSION AND ANTI-OXIDATION POWER

BRAKE FLUID DOT 5.1 is miscible with other synthetic fluids such as DOT 3, DOT 4 and DOT 5.1, except silicone based DOT 5.1 and special liquids LHM...

- Very high performance fluid.
- Absolute operational safety: immediate response in intensive use.
- Miscible in all proportions with fluids that meet the same standards.

Density at 15 °C	1,06 g/ml
Dry boiling point	260 °C min.
Wet boiling point	180 °C min.
Viscosity at -40°C	< 900 cSt

According to:

FM VSS 116 DOT 5.1 (no silicon base), DOT 4 y DOT 3
SAE J1704, ISO 4925

Rev.07/18