



COMPANÍA GENERAL DE LUBRICANTES SA

C/ Comercio, 36 – Polígono Industrial Can Sunyer
08740 SANT ANDREU DE LA BARCA (Barcelona)
Telf: +34 93 6821514 – Fax: +34 93 6820055
e-mail: gro@cogelsa.com

TECHNICAL DATA SHEET

GEAR LUBE 80W90 LS

GLOBAL RACING OIL GEAR LUBE 80W90 LS is a lubricant for gearboxes specially developed for lubricating limited slip differentials.

GEAR LUBE 80W90 LS can be used in all applications requiring a high degree of extreme pressure properties such as specifically high offset gear and pinion sets.

GEAR LUBE 80W90 LS is suitable for efficient lubrication of limited slip differentials of self blocking axles.

GEAR LUBE 80W90 LS reduces considerably noise and vibrations levels which results when pinions and various components of limited slip differentials are engaged at different speeds.

GEAR LUBE 80W90 LS gives you the following advantages:

- Prevents noise and vibrations under intensive use
- Thanks to its extreme pressure additives it provides maximum protection of very high load gears and gears subject to shocks
- Excellent compatibility with the disk friction materials
- Excellent performance with respect to seals

Density at 15 °C	0,882
Viscosity at 40 °C	175 cSt
Viscosity at 100 °C	17 cSt
Viscosity Index	mín.100
Flash point	250°C
Test 4 bearings EP (ASTMD2783)	
Weld load, minimum	400 Kg.
Copper corrosion test (ASTM-D-130)	Máximum 1B
Color	Amber

According to:

API GL-4, GL-5 LS, MT1/ SAE J2360/ MACK GO-J

Rev: 02/17

Assessment with respect to the elaboration and utilization of “plannings” for the control and conservation of plants and industrial equipment. COMPANÍA GENERAL DE LUBRICANTES S.A. is not accountable for the legal actions arised from the inadequate use of the product or products, herein referred to, being, according to our criteria, correct and complying with the quoted DESCRIPTIONS and APPLICATIONS contained herein.

COMPANY CERTIFIED

