

GEAR LUBE SAE 90 EP

Lubricant formulated with high quality paraffinic oils.

GEAR LUBE SAE 90 EP consistent oils formulated on the basis of mineral oil and special additives that increase their performance under high pressure, high temperatures and high speeds. Recommended for gears, transmissions and gearboxes.

GEAR LUBE SAE 90 EP offers the following advantages:

- Excellent temperature stability of the additives, allowing longer oil change intervals, reduced deposit formation and increased protection of mechanical components.
- Good anti-foaming, anti-corrosive and anti-oxidant properties to maintain optimum lubrication, even if contaminants such as air and water have invaded the oil.
- High anti-wear and load carrying capacity, preventing premature wear due to shock loads and heavy use.
- High viscosity index minimising the effect of temperature on oil viscosity and ensuring the permanence of the lubricating oil film at high temperatures caused by intensive and/or continuous service.

PACKAGE: 1000L / 200L / 50L / 20L / 5L

VISCOSITY AT 40 °C: 225 cSt

VISCOSITY INDEX (mín.): 95

POUR POINT: -18 °C

FLASH POINT: 250 °C

DENSITY AT 20 °C: 0,889 gr/cm³

COLOUR: Dark amber

MEETS THE STANDARDS:

API GL-4; USS STEEL 224; AGMA 250.04

REV.10/20

