



COMPANIA GENERAL DE LUBRICANTES SA

C/ Comercio, 36 – Polígono Industrial Can Sunyer
08740 SANT ANDREU DE LA BARCA (Barcelona)
Telf: +34 93 6821514 – Fax: +34 93 6820055
e-mail: gro@cogelsa.com

TECHNICAL DATA SHEET

GEAR TRANS 10W40

GEAR TRANS 10W40 offers the latest in protection for transmissions and cardan joints. Especially designed for these applications, it is a high-performance oil in all aspects related to clutch and gearbox lubrication.

GEAR TRANS 10W40 contains Extreme Pressure additives that absorb strong impact loads, which are frequent in transmissions, especially when changing gears and during acceleration and deceleration. The extreme resistance of the film prevents metal-on-metal contact in gear teeth. Its high strength translates into less friction, less wear and a reduced temperature. This means more effective power transfer and a longer life.

GEAR TRANS 10W40 is highly stable against shear fracture, and it impedes the rapid destruction of its additives. It also has extremely high thermal stability, which gives it good tensile strength and prevents the formation of foam.

GEAR TRANS 10W40 is completely compatible with the wet clutches that are present on most motorcycles, thereby extending the life of the components.

Density at 15° C	0.865
Viscosity at 40° C	105 cSt
Viscosity at 100° C	14,5 cSt
Viscosity index, minimum	142
Flash point	220° C
Fire point	250° C
Four-Ball EP Test (ASTM-D2783)	
Weld load, min.	160 kg.
Copper corrosion test (ASTM-D-130)	
3 hours at 100° C	1 b maximum
Colour	Red

For use in transmissions with the clutch immersed in oil.

Meets the specifications of: Honda, Yamaha and Suzuki

Revision: 02/17

Advising with respect to the preparation and use of schedules for controlling and maintaining industrial plants and equipment. COMPANIA GENERAL DE LUBRICANTES S.A. may not be held liable for the legal actions that may arise from inadequate use of the product or products referenced herein, and in our judgement the information contained in the DESCRIPTIONS and APPLICATIONS is correct.

CERTIFIED COMPANY

