

COMPAÑIA GENERAL DE LUBRICANTES SA

C/ Comercio, 36 – Polígono Industrial Can Sunyer 08740 SANT ANDREU DE LA BARCA (Barcelona) Telf: +34 93 6821514 – Fax: +34 93 6820055 e-mail: gro@cogelsa.com

m

## **TECHNICAL DATA SHEET**

## GEAR TRANS 80W90

**GEAR TRANS 80W90** offers the latest in transmission and cardan protection. Specially designed for these applications, it is a high-performance oil in all aspects of clutch and gearbox lubrication.

**GEAR TRANS 80W90** contains Extreme Pressure additives that absorb the heavy impact loads that are common in transmission, especially during gear shifting, acceleration and deceleration. The extreme resistance of its film prevents metal-to-metal contact on the gear teeth. Its high power results in less friction, less wear and lower temperature. This means more efficient power transmission and longer life.

**GEAR TRANS 80W90** is very stable to shear rupture and prevents rapid destruction of additives. It also has an extremely high thermal stability that allows it to resist rupture well and avoid foaming.

**GEAR TRANS 80W90** is fully compatible with the submerged clutches found on most motorcycles, extending the life of their components.

Density at 15° C	0.882
Viscosity at 40° C	175 cSt
Viscosity at 100° C	17 cSt
Viscosity index, minimum	100
Flash point	250° C
Four-Ball EP Test (ASTM-D2783)	
Weld load, min.	315 kg.
Copper corrosion test (ASTM-D-130)	
3 hours at 100° C	1 b maximu
Colour	Amber

For use in transmissions with the clutch immersed in oil.

Comply with the rules: API GL4/GL5

Revision: 01/18

## **CERTIFIED COMPANY**

