



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

# GEAR TRANS 85W140

## Mineral gear lubricant

### DESCRIPTION

Specially designed for these applications, it is a high performance oil for all aspects of clutch and gearbox lubrication, offering the ultimate in transmission and cardan shaft protection.

### PERFORMANCE

**STANDARDS:** API GL-4 / GL-5

Contains Extreme Pressure additives that absorb the heavy impact loads frequently encountered in transmissions, especially during gear shifting and acceleration and deceleration. Extreme film strength prevents metal-to-metal contact on gear teeth. Its high power translates into less friction, lower wear and reduced temperature. This means more efficient power transmission and longer life.

Very shear stable and prevents rapid destruction of the additives. It also has an extremely high thermal stability which allows it to resist breakage well and prevents foaming

### CONDITIONS OF USE

Maintenance interval according to each manufacturer's recommendations and adapted to its own use.

### TECHNICAL FEATURES

<b>SAE VISCOSITY:</b>	85W-140	<b>FREEZING POINT:</b>	-30 °C / -22 °F
<b>DENSITY AT 15 °C:</b>	0.890	<b>FLASHPOINT:</b>	260 °C / 500 °F
<b>VISCOSITY AT 100 °C:</b>	27 mm <sup>2</sup> /s	<b>TEST 4 EP BALLS (welding):</b>	315 Kg
<b>VISCOSITY AT 40 °C:</b>	320 mm <sup>2</sup> /s		
<b>VISCOSITY INDEX:</b>	112		

Rev. 01/23



[www.globalracingoil.com](http://www.globalracingoil.com)

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME  
Lubricant por 196 1919

