

TECHNICAL DATA SHEET



GLOBAL DESMO RACING 15W50

100% synthetic high performance lubricant for 4-stroke engines and 2-stroke gearboxes.

Lubricant formulated with exclusive high performance 100% synthetic bases. It exceeds the requirements of 4-stroke and 2-stroke engines that normally work at high revolutions.

GLOBAL DESMO RACING 15W50 is formulated with the finest and most exclusive synthetic bases, exceeding the performance requirements of gasoline engines. It is especially recommended for competition engines, and for those of severe and intensive use. Due to its new generation additives, **GLOBAL DESMO RACING 15W50** is also recommended for high performance 2-stroke gearboxes.

- Perfect fluidity
- Very low freezing point.
- Maximum resistance in high temperatures.
- Maximum protection of the mechanical elements.
- High viscosity index
- Low coefficient of friction

PACKAGE: 10001 / 501 / 41 / 11

VISCOSITY AT 100 °C: 19,1 cSt

VISCOSITY AT 40 °C: 127,5 cSt

VISCOSITY INDEX (mín.): 170

POUR POINT: -40 °C

FLASH POINT: 225 °C

TBN: 6,2

COLOUR: Blue

MEETS THE STANDARDS:

JASO MA-MA2; API SN

REV.02/22





