



COMPANIA GENERAL DE LUBRICANTES SA

C/ Comercio, 36 – Polígono Industrial Can Sunyer
08740 SANT ANDREU DE LA BARCA (Barcelona)
Telf: +34 93 6821514 – Fax: +34 93 6820055
e-mail: gro@cogelsa.com

TECHNICAL DATA SHEET

GLOBAL FACTORY 0W30

GLOBAL FACTORY 0W30 is a 100% synthetic high performance lubricant based on tri-ester technology. It is designed for any 4-stroke engine looking for maximum performance.

GLOBAL FACTORY 0W30 is formulated with exclusive 100% synthetic bases and specially selected additives, recommended for racing and street engines subjected to high stresses and high operating temperatures. Under these conditions, it helps to reduce the internal wear of the various engine components thanks to the protective lubricant film left on each component.

GLOBAL FACTORY 0W30 helps improve performance due to its low viscosity, which directly affects low internal friction, maintaining optimum pressure in the lubrication system.

Developed under the cooperation of Davol Tecnologic.

Clasificación SAE **0W30**

| | |
|--------------------|--------------------------|
| Viscosity at 100°C | 10,2 cSt |
| Viscosity at 40°C | 53 cSt |
| Viscosity Index | 190 |
| Pour point | -45°C |
| Flash point | 212°C |
| TBN | 6 |
| Density | 0,861 gr/cm ³ |
| Color | yellow |

Meets the following standards:

JASO MA2
API SN

REV: 09/19

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice.
Such information does not release the user from testing the product in their own application.
The data indicated represent average values and do not constitute product specifications.
For more information please contact COGELSA Technical Support.

COMPANY CERTIFIED

