



## COMPANIA GENERAL DE LUBRICANTES SA

C/ Comercio, 36 – Polígono Industrial Can Sunyer  
08740 SANT ANDREU DE LA BARCA ( Barcelona )  
Telf: +34 93 6821514 – Fax: +34 93 6820055  
e-mail: gro@cogelsa.com

## TECHNICAL DATA SHEET

### GLOBAL FACTORY 10W60

**GLOBAL FACTORY 10W60** is a 100% synthetic high performance lubricant based on tri-ester technology. It is designed for any 4-stroke engine looking for maximum performance.

**GLOBAL FACTORY 10W60** is formulated with exclusive 100% synthetic bases and specially selected additives, recommended for racing and street engines subjected to high stresses and high operating temperatures. Under these conditions, it helps to reduce the internal wear of the various engine components thanks to the protective lubricant film left on each component.

**GLOBAL FACTORY 10W60** meets the requirements of powerful motocross and enduro engines (KTM, Husqvarna, Yamaha, etc.) as well as on-road engines.

Developed under the cooperation of Davol Tecnologic.

#### Clasificación SAE **10W60**

Viscosity at 100°C	23,7 cSt
Viscosity at 40°C	158 cSt
Viscosity Index	181
Pour point	-40°C
Flash point	220°C
TBN	9
Density	0,866 gr/cm <sup>3</sup>
Color	yellow

#### Meets the following standards:

JASO MA2  
API SN

REV: 09/19

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice.  
Such information does not release the user from testing the product in their own application.  
The data indicated represent average values and do not constitute product specifications.  
For more information please contact COGELSA Technical Support.

COMPANY CERTIFIED

