



## COMPANIA GENERAL DE LUBRICANTES SA

C/ Comercio, 36 – Polígono Industrial Can Sunyer  
08740 SANT ANDREU DE LA BARCA ( Barcelona )  
Telf: +34 93 6821514 – Fax: +34 93 6820055  
e-mail: gro@cogelsa.com

## TECHNICAL DATA SHEET

### GLOBAL FLEET 10W40 E – 7

**GLOBAL FLEET SAE 10W40 E-7** is a long life synthetic oil lubricant for Diesel engines with or without turbocompressor, with maximum effectiveness at average and extreme temperatures. Specially appropriated for engine lubrication of trucks, buses, public works machinery, etc...

#### Properties:

- SAE 10W40 multigrade
- High level of detergency and dispersancy
- Maximum antiwear characteristics.
- Low friction coefficient.
- Very high shear resistance
- Meets several tests from CATERPILLAR, DAF, DEUTZ, MWM, INDENOR,ETC.

#### Advantages:

- High alkalinity reserve
- High detergent power
- Reduces fuel consumption
- Reduces maintenance costs

SAE Classification Degree	10W40
Viscosity at 100°C	15 cst
Viscosity at 40°C	110 cst
Index of viscosity	150
Pourt point	-30°C
Flash point	225°C
TBN	9,5

#### **It meets standards:**

API-CI4/CH4/CG4/CF4/CF/SL

ACEA – A3/B3/E3/E5/E7

MB-228.3 – 229.1

MAN 3275 – MACK EO-N/EO-M PLUS - VOLVO VDS-3 – MTU TYPE 2 - RENAULT RLD-2

CUMMINS 20076/20077/20078 – CATERPILLAR ECF-1-a/ECF-2

DETROIT DIESEL DDC 93K215 – DEUTZ DQC-III-10

Revision : 02/17

Assessment with respect to the elaboration and utilization of “plannings” for the control and conservation of plants and industrial equipment. COMPANIA GENERAL DE LUBRICANTES S.A. is not accountable for the legal actions arised from the inadequate use of the product or products, herein referred to, being, according to our criteria, correct and complying with the quoted DESCRIPTIONS and APPLICATIONS contained herein.

**COMPANY CERTIFIED**

