



**COMPANIA GENERAL DE LUBRICANTES SA**

C/ Comercio, 36 – Polígono Industrial Can Sunyer  
 08740 SANT ANDREU DE LA BARCA ( Barcelona )  
 Telf: +34 93 6821514 – Fax: +34 93 6820055  
 e-mail: gro@cogelsa.com

**TECHNICAL DATA SHEET**

**GLOBAL GREASE - 2**

**GLOBAL GREASE -2**, is a mineral base grease with lithium, ideal for the lubrication of any type bearings or other mechanisms working under severe conditions such as heavy loads, vibrations, shocks, high and medium speeds. Grease with multiple utilizations formulated for any type of articulations, chassis, general automobile lubrication, flat bearings, rolling bearings working under heavy loads etc. in order to be used in:

Industrial heavy equipment, lamination trains, spark plugs, bearings, trucks, buses, wheels of type 5ª, chassis, equipment used in public works, agricultural equipment, machinery used in paper manufacturing, of cement, etc.

**GLOBAL GREASE -2** has the following properties:

- Excellent resistance to water.
- Highly resistant to all metals and alloys.
- Wide range of temperature in use.
- Keeps its stability after use.
- Very good anti-rust and anti-corrosion properties.
- Very high dropping point.

		<i>Values</i>
Aspect		Light brown
NLGI	ASTM D-217	2
Dropping point °C	ASTM D-566	200
Penetration at 25 °C (mm x 10 <sup>-1</sup> ):		
-A 60 percussions	ASTM D-217	285
-A 10 <sup>5</sup> percussions, variation	ASTM D-217	-20 a +45
Welding load ( four ball test)	ASTM D-2596	160 Kg.
Ash, %	ASTM D-128	< 0,65
Range Temperature °C		- 20 to +120

Revision 02/17

Assessment with respect to the elaboration and utilization of “plannings” for the control and conservation of plants and industrial equipment. COMPANIA GENERAL DE LUBRICANTES S.A. is not accountable for the legal actions arised from the inadequate use of the product or products, herein referred to, being, according to our criteria, correct and complying with the quoted DESCRIPTIONS and APPLICATIONS contained herein.

**COMPANY CERTIFIED**

