



COMPANÍA GENERAL DE LUBRICANTES SA

C/ Comercio, 36 – Polígono Industrial Can Sunyer
08740 SANT ANDREU DE LA BARCA (Barcelona)
Telf: +34 93 6821514 – Fax: +34 93 6820055
e-mail: gro@cogelsa.com

TECHNICAL DATA SHEET

GLOBAL GREASE EP – 2

GREASE FOR MECHANISMS SUBJECT TO HEAVY LOADS

Description and applications:

Lithical grease with EP additives (Extreme Pressure) for any mechanism subject to heavy loads and high temperatures. Specially indicated in:

- ⇒ Lamination trains
- ⇒ Mechanisms subject to loads and intermittent shocks
- ⇒ Points where a multipurpose EP grease is required.
- ⇒ Reducers of gears subject to heavy loads.

Properties:

- High anticorrosive power
- High stability to oxidation
- Good mechanical stability.
- High resistance to loads

Technical characteristics:

	<i>Method</i>	<i>Values</i>
Apearance		Brown grease
Dropping point, °C	ASTM D-566	190
Penetration at 25 °C 60 percussions, mm x 10 ⁻¹	ASTM D-217	280
Variation at 10 ⁵ percussions	ASTM D-217	+ 35
Oil Separation (100°C) %	ASTM D-6184	3,5
Four ball test – weld load Kg	ASTM D-2596	315
Timken load, lb	ASTM D-2782	> 50

Revision 02/17

Assessment with respect to the elaboration and utilization of “plannings” for the control and conservation of plants and industrial equipment. COMPANÍA GENERAL DE LUBRICANTES S.A. is not accountable for the legal actions arised from the inadequate use of the product or products, herein referred to, being, according to our criteria, correct and complying with the quoted DESCRIPTIONS and APPLICATIONS contained herein.

COMPANY CERTIFIED

