

COMPAÑIA GENERAL DE LUBRICANTES SA

C/ Comercio, 36 – Polígono Industrial Can Sunyer 08740 SANT ANDREU DE LA BARCA (Barcelona) Telf: +34 93 6821514 – Fax: +34 93 6820055 e-mail: gro@cogelsa.com

TECHNICAL DATA SHEET

GLOBAL RACING 10W50

GLOBAL RACING 10W50 is a high performance 100% synthetic lubricant, which offers maximum efficiency and protection in the sector of motorcycles and quads.

GLOBAL RACING 10W50 is formulated with the finest and most exclusive synthetic bases, outrunning the requirements of gasoline, being specially recommended for racing engines, or for those having severe and intensive use. The final result is a lubricant that offers incomparable antiwear properties and gives the maximum effectiveness in a wide range of temperatures.

GLOBAL RACING 10W50 possesses some unique characteristics due to its synthetic formula, having the following characteristics:

- Perfect fluidity.
- Very low frost point.
- Maximum resistance at high temperatures.
- Maximum protection of the mechanic elements.
- High viscosity index.
- Low rubbing index.

SAE Classification	10W50
Color	blue
Viscosity at 100°C	18 cSt
Viscosity at 40°C	120 cSt
Index of viscosity	167
Pour point	-35°C
Flash point	227°C
TBN	6,2

In accordance with the exigencies: GAS-GAS, YAMAHA, SUZUKI, HONDA, KAWASAKI.

According to:

API-SN

JASO - MA 2 (Cod. JASO M034COG174)

Rev: 03/17

