



COMPANIA GENERAL DE LUBRICANTES SA

C/ Comercio, 36 – Polígono Industrial Can Sunyer
08740 SANT ANDREU DE LA BARCA (Barcelona)
Telf: +34 93 6821514 – Fax: +34 93 6820055
e-mail: gro@cogelsa.com

TECHNICAL DATA SHEET

GLOBAL RACING 5W40

GLOBAL RACING 5W40 is a high performance 100% synthetic lubricant, which offers maximum efficiency and protection in the sector of motorcycles and quads.

GLOBAL RACING 5W40 is formulated with the finest and most exclusive synthetic bases, outrunning the requirements of gasoline, being specially recommended for racing engines, or for those having severe and intensive use. The final result is a lubricant that offers incomparable antiwear properties and gives the maximum effectiveness in a wide range of temperatures.

GLOBAL RACING 5W40 possesses some unique characteristics due to its synthetic formula, having the following characteristics:

- Perfect fluidity.
- Very low frost point.
- Maximum resistance at high temperatures.
- Maximum protection of the mechanic elements.
- High viscosity index.
- Low rubbing index.

SAE Classification	5W40
Color	blue
Viscosity at 100°C	14,1 cSt
Viscosity at 40°C	90 cSt
Index of viscosity	162
Pour point	-50°C
Flash point	225°C
TBN	6,2

In accordance with the exigencies: GAS-GAS, YAMAHA, SUZUKI, HONDA, KAWASAKI.

According to:
API-SN
JASO – MA2

Rev: 03/17

Assessment with respect to the elaboration and utilization of “plannings” for the control and conservation of plants and industrial equipment. COMPANIA GENERAL DE LUBRICANTES S.A. is not accountable for the legal actions arised from the inadequate use of the product or products, herein referred to, being, according to our criteria, correct and complying with the quoted DESCRIPTIONS and APPLICATIONS contained herein.

COMPANY CERTIFIED

