

COMPAÑIA GENERAL DE LUBRICANTES SA

C/ Comercio, 36 – Polígono Industrial Can Sunyer 08740 SANT ANDREU DE LA BARCA (Barcelona) Telf: +34 93 6821514 – Fax: +34 93 6820055 e-mail: gro@cogelsa.com

TECHNICAL DATA SHEET

GLOBAL SCOOTER 4T 0W30

GLOBAL SCOOTER 4T 0W30 is a 100% synthetic, high-performance SAE 0W30 lubricant that is especially designed for all 4-stroke scooter engines of the Piaggio group, engines that are subjected to the toughest start-stop conditions, in both the city and on the highway. (JASO MB level)

GLOBAL SCOOTER 4T 0W30 is formulated with special additives that give it high chemical stability and resistance to oxidation. With a high detergent power, it keeps the engine clean and free from carbonaceous deposits. Its high fluidity allows rapid starts, even at low temperatures.

GLOBAL SCOOTER 4T 0W30 has excellent anti-wear properties that reduce friction, extend the engine' s life and notably reduce maintenance costs.

It meets the scooter engine specifications of the Piaggio group.

Not suitable for engines with a wet clutch.

SAE classification	0W30
Viscosity at 100° C	10,5 cSt
Viscosity at 40° C	52,8 cSt
Viscosity index	192
Freezing point	-45° C
Flash point	212° C
TBN	6,2

Meets the following standards:

API SN

REV: 07/18

COMPANY CERTIFIED

ISO 9001 ISO 14001 BUREAU VERITAS Certification

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications.

For more information please contact COGELSA Technical Support.