



COMPANIA GENERAL DE LUBRICANTES SA

C/ Comercio, 36 – Polígono Industrial Can Sunyer
08740 SANT ANDREU DE LA BARCA (Barcelona)
Telf: +34 93 6821514 – Fax: +34 93 6820055
e-mail: gro@cogelsa.com

TECHNICAL DATA SHEET

GLOBAL SCOOTER 4T 10W40

GLOBAL SCOOTER 4T is a lubricant that uses SAE 10W40, high-performance synthetic bases, especially designed for all 4-stroke scooter engines subjected to the toughest start-stop conditions, in both the city and on the highway.

GLOBAL SCOOTER 4T is formulated with special additives that give it high chemical stability and resistance to oxidation. With a high detergent power, it keeps the engine clean and free from carbonaceous deposits. Its high fluidity allows rapid starts, even at low temperatures.

GLOBAL SCOOTER 4T has excellent anti-wear properties that reduce friction, extend the engine's life and notably reduce maintenance costs.

Formulated for all types of situations and climates. Meets the **API (American Petroleum Institute) SL specification**. It thus exceeds the API recommended by the majority of SCOOTER manufacturers (API SH) by up to three points.

Not suitable for engines with a wet clutch.

Technical characteristics:

SAE grade	10W40
Density at 15° C	0,87
Viscosity at 40° C	110
Viscosity at 100° C	15
Viscosity index	150
Pour point	-30
Flash point	225
TBN	10

Meets the following standards:

API-SL

Revision: 03/17

Advising with respect to the preparation and use of schedules for controlling and maintaining industrial plants and equipment. COMPANIA GENERAL DE LUBRICANTES S.A. may not be held liable for the legal actions that may arise from inadequate use of the product or products referenced herein, and in our judgement the information contained in the DESCRIPTIONS and APPLICATIONS is correct.

CERTIFIED COMPANY

