



## COMPANIA GENERAL DE LUBRICANTES SA

C/ Comercio, 36 – Polígono Industrial Can Sunyer  
08740 SANT ANDREU DE LA BARCA ( Barcelona )  
Telf: +34 93 6821514 – Fax: +34 93 6820055  
e-mail: gro@cogelsa.com

## TECHNICAL DATA SHEET

### GLOBAL SMART 15W50

**GLOBAL SMART 15W50** is a high performance synthetic lubricant, which offers maximum efficiency and protection in the sector of motorcycles and quads.

**GLOBAL SMART 15W50** is formulated with the finest and most exclusive synthetic bases, outrunning the requirements of gasoline, being specially recommended for racing engines, or for those having severe and intensive use. The final result is a lubricant that offers incomparable antiwear properties and gives the maximum effectiveness in a wide range of temperatures.

**GLOBAL SMART 15W50** possesses some unique characteristics due to its synthetic formula, having the following characteristics:

- Perfect fluidity.
- Very low frost point.
- Maximum resistance at high temperatures.
- Maximum protection of the mechanic elements.
- High viscosity index.
- Low rubbing index.

	<b>Norm</b>	<b>Typical Values</b>
Density at 15 °C	ASTM D-1298	0,875
Viscosity at 40°C	ASTM D-445	139
Viscosity at 100°C	ASTM D-445	18,5
Index of viscosity	ASTM D-2270	150
Pour point °C	ASTM D-97	-30
Flash point °C	ASTM D-92	250
TBN		6,2
Sulphated ash	ASTM D-874	0,8

Additives Detergents, dispersers, antiwear, antioxidants, anticorrosives, antifoamers and frost point depressors.

**It complies with the following standards:**

API-SN

JASO – MA 2

Rev: 03/17

Assessment with respect to the elaboration and utilization of “plannings” for the control and conservation of plants and industrial equipment. COMPANIA GENERAL DE LUBRICANTES S.A. is not accountable for the legal actions arised from the inadequate use of the product or products, herein referred to, being, according to our criteria, correct and complying with the quoted DESCRIPTIONS and APPLICATIONS contained herein.

**COMPANY CERTIFIED**

