



COMPAÑIA GENERAL DE LUBRICANTES SA

C/ Comercio, 36 – Polígono Industrial Can Sunyer
08740 SANT ANDREU DE LA BARCA (Barcelona)
Telf: +34 93 6821514 – Fax: +34 93 6820055
e-mail: gro@cogelsa.com

TECHNICAL DATA SHEET

GLOBAL SPIRIT 20W50

GLOBAL SPIRIT 20W50 is a multigrade oil that exceed the latest industry standards required in today's engines.

GLOBAL SPIRIT 20W50 maintain overall engine cleanliness preventing the build up of harmful deposits, sludge and varnish; and fight wear and corrosion under a variety of driving conditions. Improved lubrication at normal and high temperatures.

GLOBAL SPIRIT 20W50 has been formulated for four strokes motors and satisfies the requirements of motorcycles engine manufactures, refrigerated as much by air as by cooling liquid, and so in transmissions.

TECHNICAL PROPERTIES:

	Norm	Typical Values	Units
Color		Amber(3,5)	-
Density at 15°C	ASTM D-1298	0,885	Kg/Lt
Viscosity at 40°C	ASTM D-445	159	mm ² /s
Viscosity at 100°C	ASTM D-445	18,7	mm ² /s
Viscosity Index	ASTM D-2270	130	-
Pour point	ASTM D-97	-24	°C
Flash Point	ASTM D-92	250	°C
Base oil		Paraffinic	-

According to the exigencies: HONDA, YAMAHA, SUZUKI, KAWASAKI, BMW.

It compiles with:

API SN
JASO – MA 2

Rev: 03/17

Assessment with respect to the elaboration and utilization of “plannings” for the control and conservation of plants and industrial equipment. COMPAÑIA GENERAL DE LUBRICANTES S.A. is not accountable for the legal actions arised from the inadequate use of the product or products, herein referred to, being, according to our criteria, correct and complying with the quoted DESCRIPTIONS and APPLICATIONS contained herein.

COMPANY CERTIFIED

