



COMPANIA GENERAL DE LUBRICANTES SA

C/ Comercio, 36 – Polígono Industrial Can Sunyer
08740 SANT ANDREU DE LA BARCA (Barcelona)
Telf: +34 93 6821514 – Fax: +34 93 6820055
e-mail: gro@cogelsa.com

TECHNICAL DATA SHEET

GLOBAL SYNT 10W40

GLOBAL SYNT 10W40 is a high performance synthetic lubricant for 4-strokes engines (gasoline and Diesel) that offers high film resistance and high load support.

GLOBAL SYNT has been created from synthetic bases carefully selected to offer antiwear protection at the superior level of conventional oils, reduces friction and wear and improves engine cooling.

This results in a higher operation effectiveness, excellent acceleration power, as well as fuel consumption reduction., expanding the life span of the engine.

Classification SAE	10W40
Viscosity at 100°C	15 cSt
Viscosity at 40°C	110 cSt
Index of Viscosity	150
Frost point	-33°C
Ignition point	225°C
TBN	9,3

In accordance with the exigencies: AUDI, BMW, CITROEN, CHRISLER, DAIMLER-BENZ, FIAT, JAGUAR, LADA, PEUGEOT, PRSCHE, RENAULT, ROLLS ROYCE, ROVER, SAAB, SEAT, VOLKSWAGEN, VOLVO, HONDA, NISSAN, TOYOTA, MITSUBISHI, DAIHATSU, SUZUKI, MAZDA, SUBARU.

It complies with the norms:

API-SL/SM/SN/CF

ACEA A5/B5

MB – 229,3/229,5/226,5 – RENAULT RN0700/RN0710 – PORCHE - GM-LL-A-025/GM-LL-B-025 - VW 502.00 – 505.00

PSA B712296 – WSS-M2C913-C

REV: 02/17

Assessment with respect to the elaboration and utilization of “plannings” for the control and conservation of plants and industrial equipment. COMPANIA GENERAL DE LUBRICANTES S.A. is not accountable for the legal actions arised from the inadequate use of the product or products, herein referred to, being, according to our criteria, correct and complying with the quoted DESCRIPTIONS and APPLICATIONS contained herein.

COMPANY CERTIFIED

