

COMPAÑIA GENERAL DE LUBRICANTES SA

C/ Comercio, 36 – Polígono Industrial Can Sunyer 08740 SANT ANDREU DE LA BARCA (Barcelona) Telf: +34 93 6821514 – Fax: +34 93 6820055 e-mail: gro@cogelsa.com

# **TECHNICAL DATA SHEET**

## GLOBAL SYNT 15W50

**GLOBAL SYNT 15W50** is a lubricant specially formulated to prevent excessive or premature engine deterioration due to its advanced technology.

### Properties & performance:

**GLOBAL SYNT 15W50** contains an exclusive antiwear additive which offers a resistance of the film superior by far to conventional oils. This characteristic is especially useful to ensure a lubrication without deterioration in critical situations of overworking and temperature. It maintains its viscosity in a wide range of temperatures. Its physical characteristics remain unchanged all along its span life, which gives a correct lubrication at any environmental conditions.

Its high detergent-dispersant capacity prevents the formation of sludge, dirt, dust and dross deposits in the cooling areas of the motor. Due to its high antioxidant capacity, **GLOBAL SYNT 15W50** maintains its initial properties.

#### **Physical-chemical characteristics:**

Density at 15 °C
Viscosity at 40°C
Viscosity at 100°C
Index of viscosity
Pour point
Flash point

0,880 g/ml 150 cSt 18 cSt 150 -30°C 225°C

### In accordance with the standards:

ALFA ROMEO, AUDI, BMW, CITROEN, CHRYSLER, DAIMLER-BENZ, FIAT, JAGUAR, LADA, PEUGEOT, PORSCHE, RENAULT, ROLLS ROYCE, ROVER, SAAB, SEAT, VOLKSWAGEN, VOLVO, HONDA, NISSAN, TOYOTA, MITSUBISHI, DAIHATSU, SUZUKI, ISUZU, HYUNDAI, MAZDA, SUBARU.

#### It complies with the norms:

API- SL ACEA A3/B3 MB-229.1

REV: 02/19

**COMPANY CERTIFIED** 

