



COMPANÍA GENERAL DE LUBRICANTES SA

C/ Comercio, 36 – Polígono Industrial Can Sunyer
08740 SANT ANDREU DE LA BARCA (Barcelona)
Telf: +34 93 6821514 – Fax: +34 93 6820055
e-mail: gro@cogelsa.com

TECHNICAL DATA SHEET

GRO MOLYGREASE EP – 2

GLOBAL RACING OIL MOLYGREASE EP-2 is a special lithium grease, and additives of Bisulphure of molybden.

Specially indicated for mechanisms subjected to heavy loads, slidings or vibrations. Also very useful for the lubrication and general greasing of vehicles, industrial equipment, and it has the following characteristics:

- It contains special additives of bysulphure of molybden.
- Very resistant to dampness.
- Resistant to wash out by water.
- It diminishes the period of maintenance, increasing the working period.
- Very resistant to heat and cold.
- Easy pumping.
- High efficiency.

NLGI degree	2
Type of basic soap	Lithium
Drop point	188 °C
Corrosion on copper segment (ASTM D-130)	1a
Weld load approx. 4 bearings	400 Kg
Temperature of working	-20 a 140°C
Water resistance DIN 51807/1	0
Color	Black

Revision 02/17

Assessment with respect to the elaboration and utilization of “plannings” for the control and conservation of plants and industrial equipment. COMPANÍA GENERAL DE LUBRICANTES S.A. is not accountable for the legal actions arised from the inadequate use of the product or products, herein referred to, being, according to our criteria, correct and complying with the quoted DESCRIPTIONS and APPLICATIONS contained herein.

COMPANY CERTIFIED

