



COMPANIA GENERAL DE LUBRICANTES SA

C/ Comercio, 36 – Polígono Industrial Can Sunyer
08740 SANT ANDREU DE LA BARCA (Barcelona)
Telf: +34 93 6821514 – Fax: +34 93 6820055
e-mail: gro@cogelsa.com

TECHNICAL DATA SHEET

GS – 3 DIESEL 15W40

GS-3 DIESEL 15W40 is a special multigrade lubricant for turbocompressed or atmospheric diesel engines. Due to its special additive package it shows a high cleaning and dispersion capability. Specially designed for engines working at high loads and extreme temperature conditions. (Heavy Transport, Public Works Machinery and Marine Engines). Compatible with EURO I, II and III.

Properties:

GS-3 DIESEL 15W40 has been designed technologically to bring the following results:

- High thermal stability, allowing work at high temperatures.
- Superior quality. It facilitates the cold start of the engine and it improves the lubrication process in cold and hot temperatures.
- It prevents sludge formation and deposits. Low ash content.
- It prevents cylinder sleeve deterioration.
- Very resistant to tear and wear, it ensures a longer life span for engines.
- Superior antioxidant, anticorrosive, antirust and antifoaming power.
- High cleaning – dispersion capacity.

Characteristics:

SAE Degree	15W40
Viscosity at 100°C	14,4 cSt.
Viscosity at 40°C	115 cSt.
Viscosity Index	138
Pour point	-24°C
Flash point	226°C
TBN	7 mg KOH/g

It complies with the norms:

API-CF-4 / SG – MB 228,1 – MAN 271 – VOLVO VDS – MOCK EO-K/2 – MTU TYPE1
ACEA E2 – DEUTZ DQC-1-02

REV: 02/17

Assessment with respect to the elaboration and utilization of “plannings” for the control and conservation of plants and industrial equipment. COMPANIA GENERAL DE LUBRICANTES S.A. is not accountable for the legal actions arised from the inadequate use of the product or products, herein referred to, being, according to our criteria, correct and complying with the quoted DESCRIPTIONS and APPLICATIONS contained herein.

COMPANY CERTIFIED

