

## COMPAÑIA GENERAL DE LUBRICANTES SA

C/ Comercio, 36 – Polígono Industrial Can Sunyer 08740 SANT ANDREU DE LA BARCA (Barcelona) Tel.: +34 93 6821514 – Fax: +34 93 6820055 e-mail: gro@cogelsa.com

# PRODUCT TECHNICAL DATA SHEET

# GXS OW30

GXS 0W30 is a synthetic motor oil especially formulated to exceed the compatibility requirements for the gas treatment systems of all manufacturers, including both three-way catalytic converters (TCW) and particle filters (DPF or FAP). GXS 0W30 extends the life of these systems and ensures that their performance is optimum.

#### **Applications:**

Recommended for all kinds of high-performance and latest-generation gasoline and diesel engines. If offers optimum lubrication at high and low temperatures, with highly reduced engine wear due to the rapid supply of oil to lubrication points.

### **Properties and advantages:**

- Very long time between oil changes.
- Excellent detergent, dispersant and anti-wear properties.
- It provides extraordinary reduction of friction between parts, as well as reduced oxidation and corrosion, thereby allowing considerable fuel savings and therefore decreased CO2 emissions.
- It facilitates cold starts and maintains part protection, even at very high operating temperatures.

#### **Quality level**

API Service SN ACEA C2/C3

Complies with these standards: MB 229,31/229,51/229,52; VOLVO VCC RBSO-2AE; VW 502,00/505,00/505,01; BMW LONG LIFE 04; PORSCHE; GM DEXOS 2; WSS-M2C948-B; ST JLR 05.500

#### **Technical characteristics:**

0W30 SAE viscosity Density at 15° C 0.87 g/cm<sup>3</sup> Viscosity at 40° C 57 cSt Viscosity at 100° C 11.3 cSt Viscosity index 195 Flash point 210° C Freezing point -51° C Minimum TBN 9.5

The stated characteristics represent typical values.

EMPRESA CERTIFICADA

Revision: 06/17

