



COMPANÍA GENERAL DE LUBRICANTES SA

C/ Comercio, 36 – Polígono Industrial Can Sunyer
08740 SANT ANDREU DE LA BARCA (Barcelona)
Telf: +34 93 6821514 – Fax: +34 93 6820055
e-mail: gro@cogelsa.com

TECHNICAL DATA SHEET

GXS 5W30

FULLY SYNTHETIC LOW SAPS TECHNOLOGY LUBRICANT FOR DIESEL AND GASOLINE ENGINES. SPECIALLY DEVELOPED FOR VOLKSWAGEN GROUP ENGINES ACCORDING TO VW 504.00 / 507.00

Applications:

Specially formulated to meet the most recent low emission exigencies respect Euro IV standards in Diesel and gasoline engines. Developed for the new generation of VW vehicles equipped with exhaust gas treatment (DPF).

Properties and advantages:

- Low viscosity at low temperatures that ensures excellent cold start. Keeps an extraordinary film strength at high temperatures.
- Exceptional detergency, dispersancy and antiwear properties.
- Its low content in sulphur, phosphorous and ashes increases filter lifespan and reduces environment emissions in a superior value than other conventional lubricants.

Specifications:

ACEA

C3

It complies with the norms: VW 504.00/507.00, MB 229.51, BMW LL04, PORSCHE C30

Technical characteristics:

SAE classification	5 W 30
Density at 15 °C	0,86 g/cm ³
Viscosity at 40 °C	70 cSt
Viscosity at 100 °C	12 cSt
Viscosity Index	170
Flash point	210 °C
Pour point	- 48 °C
TBN	10

Rev. 02/17

Assessment with respect to the elaboration and utilization of “plannings” for the control and conservation of plants and industrial equipment. COMPANÍA GENERAL DE LUBRICANTES S.A. is not accountable for the legal actions arised from the inadequate use of the product or products, herein referred to, being, according to our criteria, correct and complying with the quoted DESCRIPTIONS and APPLICATIONS contained herein.

COMPANY CERTIFIED

