

TECHNICAL DATA SHEET



GXS 5W30 C4

100% synthetic lubricant, gasoline and diesel

GXS 5W30 C4 is a 100% synthetic LOW SAPS engine oil specially formulated to exceed the requirements of compatibility with the gas treatment systems (EGR, DPF or FAP) where an **ACEA C4** is recommended by the manufacturer. **GXS 5W30 C4** is specially designed for Renault and Nissan group engines equipped with particle filters that require the RN0720 specification, MB vehicle engines that require the MB 226.51 and Renault OM 607 specification and in general, all types of vehicle engines that require an **ACEA C4** quality and incorporate DPF-FAP particulate filters

Recommended for all types of service and especially in severe conditions.

- Its low sulphur, phosphorus and sulphated ash content extends the lifespan of catalysts and particle filters, ensuring optimum performance.
- ❖ It also contributes to the reduction of fuel consumption and CO2 emissions.
- It passes the severe oxidation test required to meet the demanding API SM specification.
- Excellent detergency, dispersion and anti-wear properties.

MEETS THE STANDARDS:

ACEA C4; API SN/CF; MB 226,51/229,51; RENAULT RN0720.

PACKAGE: 2001/501/51

VISCOSITY AT 100 °C: 12 cSt

VISCOSITY AT 40 °C: 70 cSt

VISCOSITY INDEX (mín.): 170

POUR POINT: -51 °C

FLASH POINT: 210 °C

DENSITY AT 20 °C: 0,86 gr/cm3

COLOUR: Amber

REV.10/20









