

COMPAÑIA GENERAL DE LUBRICANTES SA

C/ Comercio, 36 – Polígono Industrial Can Sunyer 08740 SANT ANDREU DE LA BARCA (Barcelona) Telf: +34 93 6821514 – Fax: +34 93 6820055 e-mail: gro@cogelsa.com

TECHNICAL DATA SHEET

GXS 5W40 - GXS 5W60

GLOBAL RACING OIL GXS is a high performance 100% synthetic lubricant, which offers maximum efficiency and protection in the sector of automobile lubricants.

GXS is formulated with the finest and most exclusive synthetic bases, outrunning the requirements of gasoline and Diesel engines, with or without turbocompressor, being specially recommended for competition engines, or for those having severe and intensive use. The final result is a lubricant that offers incomparable antiwear properties and gives the maximum effectiveness in a wide range of temperatures.

GXS possesses some unique characteristics due to its synthetic formula, having the following characteristics:

- Perfect fluidity.
- Very low frost point.
- Maximum resistance at high temperatures.
- Maximum protection of the mechanic elements.
- High viscosity index.
- Low rubbing index.

SAE Classification	5W40	5W60
Viscosity at 100°C	14,1 cSt	22 cSt
Viscosity at 40°C	90 cSt	130 cSt
Index of viscosity	162	200
Pour point	- 50 °C	- 50 °C
Flash point	225 °C	230 °C
TBN	9,5	9,5

In accordance with the exigencies: ROMEO, CITROEN, ALFA AUDI, BMW, CHRISLER, DAIMLER-BENZ, FIAT, JAGUAR, LADA, PEUGEOT, PORSCHE, RENAULT, ROLLS VOLVO, ROYCE, ROVER, SAAB, SEAT, VOLKSWAGEN, HONDA, NISSAN, TOYOTA, MITSUBISHI, DAIHATSU, SUZUKI, MAZDA, SUBARU.

It complies with the norms:

API SN/CF; ACEA A5/B5; MB 229,3/229,5/226,5; RN 0700/RN0710; VW 502/505; PORSCHE; GM-LL-A-025; PSA B712296; FORD WSS-M2C913-C.

REV.02/17

