



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

MIX-3

Synthetic lubricant for 2-stroke engines

DESCRIPTION

A lubricant that combines basic oils and additives specially formulated for 2-stroke engines, with separate lubrication or premix which promotes the formation of an extraordinarily resistant film that protects the pistons from seizing and scratching even in the most adverse conditions. Its excellent lubricity reduces temperature and wear.

PERFORMANCE

STANDARDS: API TC
JASO FC

An exceptionally clean-burning lubricant resulting in longer spark plug life, minimal build-up of carbon deposits and minimal smoke emission. It has the unique property of being able to make its own residues soluble, and as a result the engine and combustion chamber stay clean. Thanks to this residue-free combustion, the ports and exhaust valves, segments and spark plugs remain clean, avoiding the loss of power that occurs in 2-stroke engines with the use of conventional products.

CONDITIONS OF USE

When used for premixing with fuel, the engine manufacturer's recommendations should be followed for proportions.

TECHNICAL FEATURES

DENSITY AT 15°C:	0.870	FREEZING POINT:	-32°C / -25.6 F
VISCOSITY AT 100°C:	8.2 mm ² /s	FLASHPOINT:	108°C / 226.4 F
VISCOSITY AT 40°C:	60 mm ² /s	SULPHATED ASH:	n/d % Mass
VISCOSITY INDEX:	100		

Rev.12/22



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME
Subsidio por 2016-2022

