



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

SYNT 10

100% synthetic lubricant for 2-stroke engines

DESCRIPTION

A 100% synthetic-base lubricant for high-performance 2-stroke engines. Special divination that reduces friction, prevents the formation of smoke and carbon deposits, extends the life of spark plugs, and increases cooling and engine performance. Recommended for modern injection systems.

PERFORMANCE

STANDARDS: API TC+
JASO FD
ISO L-EGD

The Japanese JASO standard consists of successfully passing 4 engine tests on a test bench to measure the lubricant's capacities as a detergent, against smoke and oil deposits. The JASO FD specification is the highest level of the standard, offering improved engine performance over the JASO FC.

A formula with specific synthetic bases with high combustion power to reduce deposit formation.

It mixes immediately and remains very stable in petrol.

CONDITIONS OF USE

Mix: 2% to 4% (50:1 to 25:1) according to the manufacturers' recommendations and adapted to its own use.

TECHNICAL FEATURES

COLOUR:	Purple	FREEZING POINT:	-35°C / -31 F
DENSITY AT 15°C:	0.870	FLASHPOINT:	114°C / 237.2 F
VISCOSITY AT 100°C:	7.05 mm ² /s		
VISCOSITY AT 40°C:	45 mm ² /s		
VISCOSITY INDEX:	115		

Rev. 12/22



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME
Subsidized per 2016-2017

