

ULTRADEG WASH D50

DIRECT-USE CLEANING SOLVENT

DESCRIPTION

ULTRADEG WASH D50 is based on a highly effective detergent and surfactant agents. Substitute for solvents based on hydrocarbons, alcohols, etc.

APPLICATIONS

ULTRADEG WASH D50 is used for cleaning ferrous and non-ferrous metals to remove grease, oil and dirt in general. It is suitable for cleaning painted metal surfaces: cleaning of forklifts, cleaning of machining centres and machinery.

ULTRADEG WASH D50 is used pure or diluted with water and is applied by spraying, sponging, wiping, dipping or pressure. It allows subsequent rinsing with water..

PROPERTIES

- Does not attack surfaces: metals, plastics, paints, chrome, leather, rubber.
- Does not leave any residue.
- No unpleasant odor.
- Washable with water.
- Anticorrosive capacity.
- Gives brightness to metallic surfaces.

PRECAUTIONS

Refer to safety data sheet

CHARACTERISTICS

| | Units | Typical values | Method |
|--------------------|--------------------|--|-------------|
| Appearance | - | Clear blue liquid Slight citrus smell | - |
| Density at 15 °C | kg/dm ³ | 1,02 | ASTM D 1298 |
| Viscosity at 25 °C | cPs | 3 | ASTM D 2196 |
| Flash point | °C | Non flammable | ASTM D 92 |
| pH | - | 7,5 | ASTM D 1293 |
| Water solubility | - | soluble | - |

Rev: 11/20

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support. COGELSA is not liable for damages caused by improper use of the product.