

Outstanding Outdoor Performance

with Luxurious Features



PATHRIDER 130 XL

4-Wheel Scooter



33 cm (13")
Pneumatic Tyres



Full Suspension



Easy Drive Tiller



Full Lighting Package

The **Pathrider® 130 XL** incorporates a blend of power, style and performance to handle rugged outdoor terrain. The powerful drivetrain, 24 Volt, 4-pole motor for increased power, 11.4 cm (4.5") ground clearance and maximum speed of 10 km/h (6.2 mph) combine power and torque to accelerate your active lifestyle. Standard features include feather touch disassembly, wraparound delta tiller, 33 cm (13") pneumatic tyres, front and rear suspension, high-back reclining seat, full lighting package, infinitely-adjustable tiller, front basket and rearview mirror. Available in Red and Silver.

PATHRIDER 130 XL

Specifications 4W: S713

Weight Capacity	158.75 kg (350 lbs.)
Maximum Speed ¹	10 km/h (6.2 mph)
Ground Clearance ²	11.4 cm (4.5")
Turning Radius ²	167.6 cm (66")
Overall Length ²	135.9 cm (53.5")
Overall Width ²	63.65 cm (25")
Seat-to-floor Height	63 cm - 67 cm (25" - 26")
Front Tyres	10 cm x 33 cm (4" x 13") pneumatic
Rear Tyres	10 cm x 33 cm (4" x 13") pneumatic
Range Per Charge ^{2,4}	Up to 24.99 km (15.53 miles)
Total Weight Without Batteries	101.1 kg (223 lbs.)
Heaviest Piece When Disassembled	42.9 kg (94.5 lbs.) (front section)
Standard Seating	<i>Type:</i> CRS Deluxe <i>Weight:</i> 22.5 kg (49.5 lbs.) <i>Material:</i> Black Vinyl <i>Dimensions:</i> Width: 45 cm (18") Depth: 45 cm (18")
Motor Output	24-volt DC motor, sealed mini-transaxle
Brakes	Electronic, regenerative and electromechanical
Battery Requirements ^{3,5}	(2) 12V deep-cycle Size: (2) 55 AH (Group 24) Weight: 16.6 kg (36.5 lbs.) each
Battery Charger	Off-board, 5 amp
Colour	Mercury Silver Candy Apple Red



Features

- Large 33 cm (13") pneumatic tyres for excellent outdoor performance
- Full lighting package including directional signals and angle-adjustable, dual bulb lower LED headlight
- Seat post suspension for a smoother ride
- Easy drive tiller with wraparound handles
- Easily accessible tie down points (for transport of unoccupied scooter)
- Rearview mirror standard

Options

- Pride® rear bag (includes crutch/walking stick holder)
- Walker holder (must have Pride® rear bag to attach)
- Oxygen tank holder (must have Pride® rear bag to attach)
- Saddlebag
- Mobile phone holder
- Cup holder
- Flag

¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition. These specifications can be subject to a variance of (+/- 10%).
² Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).
³ AGM or gel cell type required.
⁴ Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
⁵ Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice.
 The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tyre pressure.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressure, ambient temperature, and the gradient and surface of the road or pavement.



20-24 Apollo Drive Hallam, Victoria 3803
 ACN 088 609 661 ABN 66 088 609 661



(Tel) 03 8770 9600 • (Fax) 03 9703 2720 • www.pridemobility.com.au

