

32ch, 16 PoE, 12MP Resolution, H.265 NVR



32ch NVR

NR324XP

- > Fully Adheres to National Defense Authorization Act (NDAA) Guidelines
- > 32ch network recorder with H.265 Compression for Best-in-Class Recording and Storage Capability
- > Supports 4 SATA HDD up to 10TB and has Embedded PoE Switch for all Video Channels
- > Supports recording of up to 12MP Resolution Images
- > Display Images up to 4K(8MP) Resolution on HDMI Output
- > Concurrent Independent Displays on HDMI and VGA Monitor Outputs
- > ONVIF Profile Series Compliant
- > Easy Plug and Play Functionality with Automatic Device Discovery and Display
- > Supports Cloud Upgrade for NVR and Cameras, with Automatic Detection of Latest Firmware and Upgrades, and is ONVIF Profile S Compliant
- > Various Panoramic, Fisheye Dewarping modes are supported for live view and playback
- > Features Automatic Network Recovery (ANR) Technology to enhance storage reliability when network is disconnected
- > Supported by uniview tec Guard Station Client Software and Guard Viewer Mobile App's for iPhone and Android Devices

www.univiewtechnology.com

Specifications

Video & Audio Inputs	
IP Video Input	32-ch
Audio Input	1-ch, RCA
Network	
Incoming Bandwidth	320Mbps
Outgoing Bandwidth	320Mbps
Remote Users	128
Protocols	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP, NFS
Supported Browsers	IE(IE10/11) for Windows; Firefox (version 52.0 and above) for Windows; Chrome(version 45 and above) for Windows; Edge(version 79 and above) for Windows
Video & Audio Outputs	
HDMI / VGA Output	HDMI: 3840 x 2160 / 30Hz, 1920 x 1080p / 60Hz, 1920 x 1080p / 50Hz, 1600 x 1200 / 60Hz, 1280 x 1024 / 60Hz, 1280 x 720 / 60Hz, 1024 x 768 / 60Hz VGA: 1920 x 1080p / 60Hz, 1920 x 1080p / 50Hz, 1600 x 1200 / 60Hz, 1280 x 1024 / 60Hz, 1280 x 720 / 60Hz, 1024 x 768 / 60Hz
Recording Resolution	12MP / 8MP / 6MP / 5MP / 4MP / 3MP / 1080p / 960p / 720p / D1 / 2CIF / CIF
Audio Output	1-ch, RCA
Audio Compression	G.711A, G.711U
Synchronous Playback	16-ch
Live view display	1 / 4 / 6 / 8 / 9 / 16 / 25 / 36
Corridor Mode Screen	3 / 4 / 5 / 7 / 9 / 10 / 12 / 16 / 32
Snapshot	
FTP/Schedule/Event Snapshot	16-ch snapshot, up to 1080P resolution
Decoding	
Decoding format	Ultra 265 / H.265 / H.264
Live view/Playback	12MP / 8MP / 6MP / 5MP / 4MP / 3MP / 1080p / 960p / 720p / D1 / 2CIF / CIF
Capability	1 x 12MP @ 30, 2 x 4K @ 30, 5 x 4MP @ 30, 10 x 1080P @ 30, 22 x 720P @ 30, 32 x D1
Hard Disk Drives	
SATA	4 SATA Interfaces
Capacity	Up to 10TB for each HDD

RAID	RAID 1, 5
Smart Features	
VCA Detection by Camera	Face Detection, Face Comparison, Intrusion Detection, Cross Line Detection, Enter Area, Leave Area, Defocus Detection, Scene Change Detection, Object Left Behind, Object Removed, Auto Tracking, Ultra Motion Detection(UMD)
VCA Search	Face Search, Face Comparison Search, Behavior Search, Vehicle Search
People counting	People Flow Counting, Crowd Density Monitoring
Smart Intrusion Prevention (SIP), Face Detection, UMD by Camera	8-ch
System Alarm	
General Alarm	Motion, Tampering, Human Body Detection, Video Loss, Alarm Input, Audio Detection
Alert Alarm	IP Conflict, Network Disconnected, Disk Offline , Disk Abnormal, Illegal Access, Hard Disk Space Low, Hard Disk Full, Recording / Snapshot Abnormal
External Interface	
Network Interface	1 x RJ45 10M/100M/1000M self-adaptive Ethernet Interface
USB Interface	Front panel: 1 x USB2.0; Rear panel: 1 x USB3.0
RS485	1
Alarm In	16-ch
Alarm Out	4-ch
PoE	
Interface	16 x RJ-45 10M/100M self-adaptive Ethernet Interface
Max Power	Max 30W for single port Max 150W in total
Supported Standard	IEEE 802.3af/at
General	
Power Supply	100~240V AC; Power Consumption: ≤ 15W (without HDD)
Working Environment	-10°C ~ + 55°C (+14°F ~ +131°F), Humidity ≤ 90% RH(non-condensing)
Dimensions (W × D × H)	400 × 363 × 74mm (15.7 × 14.3 × 2.9")
Weight (without HDD)	≤ 4Kg (8.82lb)
General	
Certifications	FCC, CE (UL – Power Supply only)



Accessories

LB3L	NVR Lockbox
4KTESTMON	Multi-Function Video Test Monitor
NSW162PX	16-Port PoE Switch

Models

NR324XP-8T	NR324XP-16T
NR324XP-24T	NR324XP-32T
NR324XP-40T	

Dimensions



Rear Panel View

