

NVR Redundant Power Supply



Power Supply

PWR-DC12-350A-IN

- > Redundant Power Supply for recorders with large quantities of hard disk drives, such as NR648XC
- > Protection against short circuit, overload & overvoltage
- > Front panel indicator lights alert to normal and abnormal conditions
- > Meets regulatory standards: UL, CE

www.univiewtechnology.com

uniview tec

UVT6620224-00

Specifications

AC Input	
Voltage	90 ~ 264VAC
Frequency	47~63 Hz
Power factor	≥0.95
Input current	≤ 6.3A @ 100-240VAC
Input protection	Input under voltage or over voltage
DC Output	
Voltage / Electricity	+12VDC/29A, +12V Standby/2.1A
Output Power	350W
Output Efficiency	≥89%, 220V AC/29A
Line & Load Regulation; Regulated Voltage Accuracy, Dynamic Response Overshoot, Current Sharing Rate	±5%
Output Protection	Short Circuit Protection, Overload Protection, Overvoltage Protection, Hot Plug Protection, Over Temperature Protection
General	
Indicator Light	Normal: green on; Abnormal: Yellow on
Working Temperature	0 ~ 50°C
Storage Temperature	-40 ~ 70°C
Heat Dissipation	Ventilating fan design, heat emission at back
Dimension (D×H×W)	185×40×73.5mm
Conformity Standards	
EMC	EN55032, EN 61000-3-2, EN55035
NEBS	SR-332 ISSUE 2
Approvals	UL, CB, FCC