ALPHA

Features:



- 24/7 Operation
- Very small slim design, with only 26 mm depth
- JAHC for scheduling ON/OFF during a week
- System bracket for VESA (Optional)
- Quad digital signal output

ALPHA SI360 is based on Intel i3 12th. generation processor. This is a top level industrial designed player, offering great value for signage and industrial tasks. Also featuring Four Display Outputs Supporting 4K Video Playback







СРU	Intel [®] Core™ i3-1215U Alder Lake TDP 12-55W, 6 cores, 10 MB Cache
Frequency	4.40 Ghz
BIOS	AMI Source code
Chipset	SOC
Memory	8 GB DDR4 SO-DIMM
GPU	Intel [®] 12th Gen. UHD Graphics
HDMI	4 x HDMI 2.0 (Max.4069x2304 @60Hz)
Network	1 x Intel® i219LM Gigabit Ethernet
USB	1 x USB 3.2 Gen2, 2 x USB 2.0
	1 x USB-C 3.2 Gen2
Serial Port	1 x RS232
Audio	1 x AUDIO-OUT, 1 x MIC-IN
Storage	250 GB NVME (M.2 2280 PCIe)

Slots	1 x M.2 2230 for WiFi/BT/3G/4G
JAHC	WatchDog Timer Auto Power On RTC
Operating System	Windows 10 LTSC 21H2
Power Req.	DC-IN, 19V/3,42A
Fanless	No
Contruction	Metal
Operation temp.	0°C ~ 40°C (32°F ~ 104°F)
Mounting (Optional)	ALPHA VESA Bracket ALPHA Wallmount with player bracket
Relative Humidity	95% @ 40°C (non-condensing)
Color	Black
Certification	CE, FCC Class B, CCC
Dimensions	189.6mm x 148.3mm x 26mm

InterSign ApS, Brunbjergvej 1, 8240 Risskov

www.inter-sign.dk

