



Styletto AX Charger

Data Sheet



Styiletto AX Charger | Technical Data

Device property		
	Dimensions (LxWxH)	70.8 x 49.9 x 29.5 mm
	Weight excluding cable	50 g
	Protection against ingress of water	IP XO (ordinary)
	Protection against electric shock	class III
Electrical property		
Charger		
	Power supply connector	USB-C
	Input voltage	5 V DC
	Input current	≤ 0.5 A
Power supply adapter		
	Input voltage	100 – 240 V AC
	Input current	0.15 – 0.3 A
	Input frequency	50 – 60 Hz
	Output voltage	5 V DC
	Output current	1 A
Charging		
	Charging time (USB)	~ 3 h
	Charging time (wireless)	~ 6 h
Built-in battery		
	Battery type	Lithium-ion polymer
	Battery capacity	400 mAh
	Battery runtime	4 days in typical use
Operating conditions		
	Temperature (USB charging)	+10 ... +35 °C / +50 ... +95 °F
	Temperature (wireless charging)	+10 ... +30 °C / +50 ... +86 °F
	Relative humidity	20 ... 75 %
	Minimum air pressure	700 hPa
Storage conditions		
	Temperature (recommended)	+10 ... +25 °C / +50 ... +77 °F
	Temperature (max.)	+10 ... +40 °C / +50 ... +104 °F
	Relative humidity (recommended)	20 ... 80 %
	Relative humidity (max.)	10 ... 80 %
Transportation conditions		
	Temperature (recommended)	-20 ... +60 °C / -4 ... +140 °F
	Temperature (max.)	-20 ... +60 °C / -4 ... +140 °F
	Relative humidity (recommended)	5 ... 90 %
	Relative humidity (max.)	5 ... 90 %
Safety / conformity		
	Safety approvals	IEC / EN 62368-1:2014
EMC	EU CE	EN 60601-1-2 4th edition
	US FCC	47CFR Part 15 (2017)
	Canada IC	ICES-003 Issue 6 (2017)
	Korea KCC	KN 32 / KN 35

Styletto AX Charger | Further information


Standards and additional information

- ▶ The battery runtime is based on the given current consumption. The actual battery runtime is determined by battery quality, usage and activated feature set.
- ▶ Styletto AX Charger is a part of the Kit Styletto AX, which also consists of Styletto AX. Please consult the data sheet Styletto AX for relevant technical information.
- ▶ Note: due to the design of the Styletto AX, not all earwear connections will fit inside Styletto AX Charger.
Recommended connections: S, M and P-Receivers (length 0–3) with Earware 3.0 open and tulip (all sizes) or sleeves (size XS–M).

Special note for instruments with built-in lithium-ion rechargeable battery

- ▶ The runtime of all lithium-ion rechargeable batteries reduces over time. The estimates are based on fresh lithium-ion rechargeable battery capacity. Under normal operating conditions, the battery will retain up to 80 % of its initial capacity after 2 years of use. Please note that battery performance will vary depending on individual usage patterns and environmental conditions.

The information in this document contains general descriptions of the technical options available, which do not always have to be present in individual cases and are subject to change without prior notice. The required features should therefore be specified in each individual case at the time of conclusion of the respective contract.

 **Legal Manufacturer**
WSAUD A/S
Nymøllevej 6
3540 Lyngø
Denmark



Order No. 04742-99T02-7600
© 08.2021, WSAUD A/S
All rights reserved

Subject to change
without prior notice



WARNING

Choking hazard posed by small parts.

- ▶ This instrument is not intended for the fitting of infants, children under 3 years or persons of mental incapacity.