










www.reymatex.net

									Optional Device				
CTD-9713-0-240M/UCP-D1	2	4	4.0 mm	1.4~3.6	1:2.9 ~ 1:0.3	5 mm	#11 mm UY128GAS	4.500 S.P.M					
CTD-9713-0-248M/UCP-D1			4.8 mm										
CTD-9713-0-356M/UCP-D1	5.6 mm												
CTD-9713-0-364M/UCP-D1	3	5	6.4 mm		1:0.7 ~ 1:2.0								
CTD-9760-0-456M/UCP-D1			5.6 mm										
CTD-9760-0-460M/UCP-D1			6.0 mm										
CTD-9760-0-464M/UCP-D1	4	6	6.4 mm										
CTD-9760-0-464M/UCP-D1			6.4 mm										

CTD-9713-0-356M/UCP-D1

OA7785D



Direct drive (Ho Hsing servo motor) small cylinder bed interlock machine with top and bottom covering threads, 3 needles gauge. Equipped with automatic pneumatic upper and lower thread trimmers and presser foot lifter. Gauge for overlock seam covering.

CTD-9713-0-356M/UCP-D1

OA7785D



Máquina de base cilíndrica pequeña (6 de ancho máximo y circunferencia de 18cm) de 3 agujas con recubrimiento superior e inferior equipada con motor Ho Hsing en el cabezal, cortahilos inferior y superior neumáticos y alzaprensatelas neumático. Para costuras planas en general.