



										Optional Device
CTU-9011-0-248M/UCP-B1/FB1	2	4	4.8 mm							
CTU-9011-0-356M/UCP-B1/FB1	3	5	5.6 mm	1.4 ~ 3.6	1:0.3 ~ 1:2.9	1:6	5 mm	#11 mm UY128GAS	5.500 S.P.M	
CTU-9011-0-364M/UCP-B1/FB1	3	5	6.4 mm							

CTU-9011-0-356M/UCP-B1/FB-1

0A7759J



Direct drive (Ho Hsing servo motor) 3 needles cylinder bed top feed transport, top and bottom cover threads interlock machine. Equipped with automatic pneumatic upper and lower thread trimmer and presser foot lifter.

Gauges available:

- Gauge: 5,2 mm 0A7799B1
- Gauge: 6 mm 0A7799B

CTU-9011-0-356M/UCP-B1/FB-1

0A7759J



Máquina de base cilíndrica de 3 agujas con recubrimiento superior e inferior de arrastre superior equipada con motor Ho Hsing en el cabezal, cortahilos inferior y superior neumáticos y alzaprensatelas neumático. Para costuras planas en general.

Galgas disponibles:

- Galga: 5,2 mm 0A7799B1
- Galga: 6 mm 0A7799B