



										Optional Device
CTU-9713-0-248M/UCP-FB1	2	4	4.8 mm							
CTU-9713-0-356M/UCP-FB1			5.6 mm	1.4 ~ 3.6	1:0.3 ~ 1:2.9	1:6	5 mm	#11 mm UY128GAS	4,500 S.P.M	• FD1
CTU-9713-0-364M/UCP-FB1	3	5	6.4 mm							

CTU-9713-0-356M/UCP-FB1

OA7785C



Direct drive (Ho Hsing servo motor) top feed small cylinder bed interlock machine with top and bottom covering threads, 3 needles gauge. Equipped with automatic pneumatic upper and lower thread trimmers and presser foot lifter. Gauge for bottom of T-shirts, polos and similar.

CTU-9713-0-356M/UCP-FB1

OA7785C



Recouvreuse canon 2/3 aiguilles à moteur incorporé (Ho Hsing) avec entraînement supérieur, recouvrement supérieur et inférieur avec coupe-fils supérieur et inférieur et relevage de pieds pneumatique. Pour couture de bas (de vestes, de pantalons).

CTU-9713-0-356M/UCP-FB1

OA7785C



Máquina de base cilíndrica pequeña (6 de ancho máximo y circunferenciada 18 cm) de 3 agujas con recubrimiento superior e inferior de arrastre superior (doble arrastre) equipada con motor Ho Hsing en el cabezal, cortahilos inferior y superior neumáticos y alzaprensatelas neumático. Para costuras planas en general.

CTU-9713-0-356M/UCP-FB1

OA7785C



Macchina a braccio piccolo ad alta velocità con copertura superiore e inferiore di 2/3 aghi (motore servo Direct Drive integrato). Dotata di rasafilo inferiore e superiore e alzapiedino pneumatico.