



- Termofijadora abierta.
- Thermoadhesive open.



- Palanca de presión.
- Pressure lever.



- Palanca de apertura y cierre.
- Opening & closing lever.



- Mesa para termofijadora con pieza antideslizante.
- Table for fusing machines PLT with non-slip part.



PL/T1250 125X50	125x50 cm	380V +N trifásico	4.250W	0-230 °C	0-90 Segundos	106 Kg Neto 129 Kg Bruto	135x100x62cm
MESA TERMOFIJADORA	BAB001					16,5 Kg Neto 18 Kg Bruto	81x46x15cm

MANUAL FUSING AND TRANSFER PL/T1250 125x50

OB4101



The thermoadhesive PL/T press, with its steel framework, is tough, safe, reliable and easy to be operated. A manual control makes possible to set the pressure of the top and the pressing time, whereas the temperature of the top is set through a digital thermostat. A safety device prevents the top from closing accidentally. The work surface is 125x50 cm. Pressure = 3 kg/cm².

TABLE FOR COMEL FUSING MACHINES BAB001



Table for with non-slip part that prevents the slip of the fusing machine. Measurements: Height 78.7x51,1x71,7 cm.

TERMOFIJADORA DE PLATO PL/T1250 125x50

OB4101



Termofijadora manual de plato PL/T con estructura de acero: es resistente, segura, fiable y fácil de utilizar. Un control manual permite ajustar la presión de la parte superior y el tiempo de prensado, mientras que la temperatura de la parte superior se ajusta a través de un termostato digital. Un dispositivo de seguridad impide que la tapa se cierre accidentalmente. El área de trabajo es de 125x50cm. Presión = 3 kg/cm²

MESA PARA TERMOFIJADORAS COMEL BAB001



Mesa para termofijadoras Comel con pieza antideslizante que impide el deslizamiento de la termofijadora de acero. Medidas: altura 78,7x51,1x71,7 cm.